

Public Address & Evacuation Horn Speakers



ATC10



ATC15



ATC30



HD35/HD60



MH30



MH5300



H16

ATC10 Horn Speaker

Equipped with a capacitor for use in systems requiring supervisory monitoring, such as emergency evacuation systems, the ATC10 delivers amazing SPL and clarity for very little money.

- > 10 watts power rating RMS
- > Adjustable wattage tapings 10, 5, 2.5, 1.25W and 8 ohm
- > Frequency response 300 Hz-8 kHz
- > 106 dB sensitivity (1W/1M)
- > 120o dispersion
- > 16.2cm diameter, 24.2cm length
- > 1.3kg
- > Metal and ABS construction

ATC15 Public Address Horn Speaker

- > IP66 rated
- > 15W power rating RMS
- > Frequency response 125 Hz-14000 Hz
- > Adjustable wattage tapings 15, 7.5, 3.75, 1.87W and 8
- > 108 dB sensitivity (1W/1M)
- > 110o dispersion
- > 3.2kg
- > Metal and ABS construction
- > Includes capacitor for EVAC purposes

ATC30 Public Address Horn Speaker

- > IP66 rated
- > 30W power rating RMS
- > Frequency response 125 Hz-14000 Hz
- > Adjustable wattage tapings 30, 15, 7.5, 3.75W and 8
- > 110 dB sensitivity (1W/1M)
- > 100o dispersion
- > 3.5kg
- > Metal and ABS construction
- > Includes capacitor for EVAC purposes

MH5300 IP66 Rated Waterproof, Dustproof

- > Rated to IP66 standard (UK) to meet the stringent requirements of industry for waterproof and dust resistant environments
- > Temperature range -30oC to +55oC
- > 30 watts power rating RMS
- > Frequency response 500 Hz – 7 kHz
- > Adjustable wattage tapings 30, 15, 7.5W
- > 107 dB sensitivity (1W/1M)
- > 100o dispersion
- > 13cm bell, 16cm height
- > 3.5kg > ABS construction
- > Available with line capacitor (MPH5300C)

MH30 Music Horn - IP46 RATED

The sonic benefits of a cone speaker with the "throw" benefits of a horn speaker.

- > 30 watts power rating RMS
- > IP46 rated
- > Adjustable tapings 30, 15, 7.5W
- > 60 x 60o dispersion
- > 101dB sensitivity (1W/1M)
- > Dimensions (mm): 234h x 283w x 256d
- > Frequency response: 125Hz – 15kHz

HD35/HD60 Horn Drivers

- > For use with H16 or HK16 flares
- > 35 watts power rating RMS (HD35)
- > 60 watts power rating RMS (HD60)
- > Frequency response 125 Hz-14000 Hz
- > Adjustable wattage tapings 35, 20, 10W (HD35); 60, 40, 20W (HD60)
- > 110 dB sensitivity (1W/1M)
- > 11.6cm diameter, 11cm length
- > 2kg > Metal construction
- > HD358 (16ohm- 35W) also available

H16 Round Flare

Round flare for use with HD35/HD60 horn driver

- > 95o dispersion
- > 42cm diameter
- > 4.5kg
- > Aluminium construction

HK16 Rectangular Flare

Rectangular flare for use with HD35/HD60 horn driver

- > 120 x 60o dispersion
- > 41cm x 26cm dimensions
- > 4.6kg
- > ABS construction
- > Sturdy fully adjustable mounting bracket



HK16

Public Address Horn Speakers

IP Rated Music Horn and Horn Speakers

HORN DRIVERS and FLARES