



CLEVERTRONICS LP LIFELIGHT RECESSED EMERGENCY



PRODUCT INFORMATION

Catalogue Number	CLIFE
Description	Lifelight, High Performance, Recessed Emergency Light with Premium Lithium Battery Technology
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling hole cut-out	85mm, 135mm (with adaptor plate)
Minimum ceiling depth	120mm, 70mm (with adaptor plate)
Operating Mode	Non-Maintained
Testing System	Manual Test Switch
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	1 LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	1.0W Standby(3.9W during first 16hr charge)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100930	1 LED Round Head Assembly & Ring - White
1550010	Battery, LP 3.2V 3.2Ah, Li-ion, 200mm lead with Bracket
8002530	Driver, PCA:LP Lifelight Driver, Zoneworks Compatible

