

1003

ZYLO



SPECIFICATIONS:

0.3 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	95	Tilt 30°	SELV	IP44	CE	Available	Oval Beam Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	----	----------	------	------	----	-----------	---------------------	--------------------	-------------------

CONSTRUCTION & DESIGN

- Very low profile recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- Low profile adjustable LED downlight with high lumen output
- Designed with distinctive lines creating a simple and contemporary downlight
- Clear tempered glass front

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Thermodynamically compact efficient heatsink design
- Efficient optical control with no harsh cut off and ultra low glare
- Compatible with an Oval Beam Lens (Datasheet Available upon Request)

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz





TECHNICAL PERFORMANCE

- 8W, 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:



PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1003-SP-3K-8W-01 or 1003-SP-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					SP	FL	WFL	VWFL
8W	3K	1003-SP-3K-8W	1003-FL-3K-8W	1003-WFL-3K-8W	-	828	697	690	696	-
	4K	1003-SP-4K-8W	1003-FL-4K-8W	1003-WFL-4K-8W	-	870	727	738	756	-
	5K	1003-SP-5K-8W	1003-FL-5K-8W	1003-WFL-5K-8W	-	845	719	711	718	-
13W	3K	1003-SP-3K-13W	1003-FL-3K-13W	-	1003-VWFL-3K-13W	1519	1274	1275	-	1270
	4K	1003-SP-4K-13W	1003-FL-4K-13W	-	1003-VWFL-4K-13W	1607	1339	1335	-	1322
	5K	1003-SP-5K-13W	1003-FL-5K-13W	-	1003-VWFL-5K-13W	1568	1312	1290	-	1296
22W	3K	1003-SP-3K-22W	1003-FL-3K-22W	-	1003-VWFL-3K-22W	2414	2023	2029	-	2011
	4K	1003-SP-4K-22W	1003-FL-4K-22W	-	1003-VWFL-4K-22W	2584	2130	2127	-	2119
	5K	1003-SP-5K-22W	1003-FL-5K-22W	-	1003-VWFL-5K-22W	2520	2070	2044	-	2058

DIM CODE		8W	13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
	Leading & Trailing edge	Std	Std	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black



OVERALL VIEW

