

1326

TONDO 162



## SPECIFICATIONS:



0.8 kg



3K and 4K



5K



Class I



IP54



CE



Available



3 Year warranty



Made in Australia

## CONSTRUCTION &amp; DESIGN

- Surface mounted LED fixed downlight
- Constructed in spun aluminium and finished in durable polyester powdercoat paint
- Recessed acrylic diffuser gives a symmetrical wide beam distribution with high lumen output and soft diffusion
- Twist Lock mounting with no visible fasteners

## OPTICAL &amp; THERMAL PERFORMANCE

- Efficient optics and thermal management provides premium optical and thermal performance
- Wide beam distribution with no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block, also compatible with a range of dimming systems
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >75,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with very low colour shift over time

## CODE ORDERING GUIDE:

PRODUCT CODE


/

DIM CODE

-

COLOUR CODE

Example: 1326-3K-13W-01 or 1326-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 93° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		93°
13W	3K	1326-3K-13W	1519	1179
	4K	1326-4K-13W	1607	1241
	5K	1326-5K-13W	1568	1215
22W	3K	1326-3K-22W	2414	1864
	4K	1326-4K-22W	2584	1962
	5K	1326-5K-22W	2520	1922

DIM CODE		13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	x	x
	Leading & Trailing edge	Std	Std

## COLOUR CODE

-01




Satin White

-06



Matte Black



115

162

