

1287

1288

MERCURY



SPECIFICATIONS:

1.5 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	185	Rot 350°	Tilt 40°	SELV	IP44	CE	5 Year warranty	Made in Australia
--------	----------------------	---------------	-----	----------	----------	------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED adjustable wall wash downlight
- Constructed in pressure die cast aluminium alloy and finished in durable polyester powder-coat paint
- Adjustable LED downlight provides a 40° tilt angle for lighting vertical displays
- Adjustable LED downlight has high lumen output due to the brilliant optical control with an ultra low glare performance
- Clear tempered glass

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote driver (refer to dimming options table)
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60Hz




TECHNICAL PERFORMANCE


- 28W or 45W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1287-SP-3K-28W-01 or 1287-SP-3K-28W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				SP	WFL	VWFL
28W	3K	1287-SP-3K-28W	1287-FL-3K-28W	1287-WFL-3K-28W	3667	3115	3165	3172
	4K	1287-SP-4K-28W	1287-FL-4K-28W	1287-WFL-4K-28W	3805	3235	3283	3291
	5K	1287-SP-5K-28W	1287-FL-5K-28W	1287-WFL-5K-28W	3447	2928	2975	2982
45W	3K	1288-SP-3K-45W	1288-FL-3K-45W	1288-WFL-3K-45W	5289	4565	4623	4602
	4K	1288-SP-4K-45W	1288-FL-4K-45W	1288-WFL-4K-45W	5493	4744	4803	4774
	5K	1288-SP-5K-45W	1288-FL-5K-45W	1288-WFL-5K-45W	4971	4291	4346	4326



DIM CODE	OPTIONS	28W	45W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
/DIM	Leading & Trailing edge	Std	✓
	Non-dimmable	×	Std

COLOUR CODE	
-01	Satin White
-06	Matte Black
-10	Bright Silver

OVERALL VIEW

