

Intimidator Spot 360X IP

HIGHLIGHTS

- Outdoor-rated moving head designed for situations where mother nature gets in the way
- Water resistant power input/output connections save setup time
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- New home position allows for smoother programming
- Durable magnesium housing is lightweight, strong and corrosion resistant
- Dual rotating prisms split the beam for great effects and cover a larger area
- ¼-turn hanging bracket allows for single or dual clamp mounting options
- Project crisp gobos from nearly any distance with the motorized focus
- Beams always remain on the dance floor using the built-in, innovative Totem mode
- Set, save, and recall 1 scene manually, directly from the full-color LCD display
- Fits best in the Intimidator Road Case



SPECIFICATIONS

- DMX Channels : 8 or 14
- DMX Connectors : 3-pin XLR
- Pan and Tilt : 540°/270°
- Pan and Tilt Ranges : 540°, 360°, 180° pan/270°, 180°, 90° tilt
- Colors : 8 + white, split colors, continuous scroll at variable speeds
- Gobos : 7 + open (6 aluminum + 1 glass), rotating, interchangeable, indexing, slot-n-lock, continuous scroll at variable speeds
- Light Source : 1 LED (cool white) 100 W, (4.3 A), 50,000 hours life expectancy
- Strobe Rate : 0 to 20 Hz
- Beam Angle : 15°
- Lumens : 4268
- IP Rating : IP65
- Power Linking : 5 units @ 120 V; 9 units @ 230 Vv
- Power and Current :
190 W, 2.4 A @ 120 V, 60 Hz
185 W, 1.4 A @ 230 V, 50 Hz
- Weight : 23 lb (10.4 kg)
- Size : 11.8 x 8.5 x 15.9 in (299 x 217 x 406 mm)
- Approvals : CE, MET, UKCA, ROHS
- Gobo Size : 24 mm outside, 20 mm image, 1.1 mm max thickness
- Prism : 5-facet linear, bi-directional at variable speeds
- Prism : 3-facet round, bi-directional at variable speeds
- Illuminance (2m) : 23,978 lux
- Illuminance (5m) : 3,836 lux
- Color Temperature : 15,000 K
- Startup Temperature : -4 °F to 113 °F (-20 °C to 45 °C)
- Operating Temperature : -22 °F to 113 °F (-30 °C to 45 °C)
- Cable Length : 5 ft (1.5 m)
- Input Voltage : 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Bracket Mounting Hole : 13 mm
- Optional Controllers : RFC, RFC-XL
- Max. Output Current : 12 A (5 units @ 120 V) (9 units @ 230 V)

WHAT'S INCLUDED

- Fixture
- Power cord
- Hanging bracket
- Quick Reference Guide