

ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3365a - MAROOCHY RSL - SPORTS BAR REFURBISHMENT


C3365a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 28 MARCH 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1		EXISTING BLACK SPORTS BAR RECESSED DOWNLIGHT			A
L2		EXISTING WHITE BACK OF HOUSE RECESSED DOWNLIGHT			A
L3	13W 3000K LED	RECESSED DOWNLIGHT C/W DALI DIMMABLE REMOTE DRIVER	BLACK	GAMMA ILLUMINATION CIMI 1094-FL-3K-13W	A
L4		EXISTING BLACK TAB RECESSED DOWNLIGHT			A
L5	3000K LED	NEW RECESSED DOWNLIGHT TO MATCH THE EXISTING ADJACENT L2 FITTING.			A
L6	13W 3000K LED	RECESSED DOWNLIGHT C/W DALI DIMMABLE REMOTE DRIVER	BLACK	GAMMA ILLUMINATION CIMI 1094-FL-3K-13W	A
L7	13W 3000K LED	RECESSED REAR BAR DOWNLIGHT C/W DALI DIMMABLE REMOTE DRIVER	BLACK	GAMMA ILLUMINATION CIMI 1094-FL-3K-13W	A
L8	3000K LED	NEW RECESSED DOWNLIGHT TO MATCH THE EXISTING ADJACENT L1 FITTING.			A
L9	13W 3000K LED	RECESSED DOWNLIGHT C/W DALI DIMMABLE REMOTE DRIVER	BLACK	GAMMA ILLUMINATION CIMI 1094-FL-3K-13W	A
L10	13W 3000K LED	RECESSED SOUND CEILING DOWNLIGHT C/W DALI DIMMABLE REMOTE DRIVER	BLACK	GAMMA ILLUMINATION RHO 1001-3K-13W	A
L11	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 400DIA LIGHT PENDANT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT BROWN	LUMEN 8 PARROT PETITE BY FORESTIER	A
L12	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 1000DIA LIGHT PENDANT C/W CUSTOM ALUMINIUM SUPPORT FRAME TO ALLOW THE FITTING TO BE HUNG OFF THE JOINERY. CONFIRM THE SUPPORT FRAME DETAILS POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT SAND	LUMEN 8 PARROT GRANDE XL BY FORESTIER	A



C3365a - MAROOCHY RSL - SPORTS BAR REFURBISHMENT


C3365a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 28 MARCH 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L13	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 600DIA LIGHT PENDANT C/W CUSTOM ALUMINIUM SUPPORT FRAME TO ALLOW THE FITTING TO BE HUNG OFF THE JOINERY. CONFIRM THE SUPPORT FRAME DETAILS POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT BROWN	LUMEN 8 PARROT GRANDE MEDIUM BY FORESTIER	A
L14	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 1000DIA LIGHT PENDANT C/W CUSTOM ALUMINIUM SUPPORT FRAME TO ALLOW THE FITTING TO BE HUNG OFF THE COLUMN. CONFIRM THE SUPPORT FRAME DETAILS POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT SAND	LUMEN 8 PARROT GRANDE XL BY FORESTIER	A
L15	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 600DIA LIGHT PENDANT C/W CUSTOM ALUMINIUM SUPPORT FRAME TO ALLOW THE FITTING TO BE HUNG OFF THE COLUMN. CONFIRM THE SUPPORT FRAME DETAILS POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT BROWN	LUMEN 8 PARROT GRANDE MEDIUM BY FORESTIER	A
L16	EXISTING CEILING RECESS DOWN LIGHT TO BE REMOVED				A
L17A	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	650DIA WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL ELEVATION	FELT LIMESTONE	EST LIGHTING WEVER & DUCRE TAPIS SOFT 2.0	A
L17B	NO LAMP	650DIA WALL EMBELLISHMENT MOUNTED AS PER THE ARCHITECTURAL ELEVATION	FELT LIMESTONE	EST LIGHTING WEVER & DUCRE TAPIS SOFT 2.1	A
L18	13W 3000K LED	RECESSED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	BLACK	GAMMA ILLUMINATION SCOOP MINI 1495-FL- 3K-13W	A
L19	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 600DIA LIGHT PENDANT SUSPENDED FROM THE CEILING CONFIRM THE DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT BROWN	LUMEN 8 PARROT GRANDE MEDIUM BY FORESTIER	A
L20	7W 3000K 240V TRAILING EDGE DIMMABLE E27 LED	DECORATIVE 1000DIA LIGHT PENDANT SUSPENDED FROM THE CEILING CONFIRM THE DROP LENGTH ON SITE WITH THE ARCHITECT	PARROT SAND	LUMEN 8 PARROT GRANDE XL BY FORESTIER	A
L21	34W 4000K LED	300 X 1200 LAY IN FLAT PLATE LED FITTING C/W REMOTE DRIVER AND A PB MOUNTING KIT	WHITE TRIM	GAMMA ILLUMINATION AXIS 1550-4K-14W PB	A




C3365a - MAROOCHY RSL - SPORTS BAR REFURBISHMENT

C3365a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 28 MARCH 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L22	14W 4000K LED	300 X 600 LAY IN FLAT PLATE LED FITTING C/W REMOTE DRIVER AND A PB MOUNTING KIT	WHITE TRIM	GAMMA ILLUMINATION AXIS 1549-4K-34W PB	A
L23	13W 3000K LED	RECESSED DOWNLIGHT C/W DALI DIMMABLE REMOTE DRIVER	BLACK	GAMMA ILLUMINATION CIMI 1094-FL-3K-13W	A
L24	RECOVER THE EXISTING 11 PENDANTS FROM THE AREA OF THE WORKS AND RELOCATE THEM TO THE NEW POSITIONS UTILISING THE EXISTING POWER SUPPLY AND CONTROL.				C
S1	12W/M 3000K LED	MULTIPLE HORIZONTAL RUNS OF FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN A FLUSH RECESS WITHIN THE REAR BAR JOINERY AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S2	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE COUNTER PELMET AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S3	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE FEATURE WALL JOINERY AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S4	NO LONGER REQUIRED				B
S5	12W/M 3000K LED	MULTIPLE RUNS OF FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE BOOTH SEATING AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A



C3365a - MAROOCHY RSL - SPORTS BAR REFURBISHMENT


C3365a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 28 MARCH 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S6	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE SUSPENDED CEILING FEATURE AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S7	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S8	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE WITHIN THE JOINERY KICK AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP LOCATED IN A CONCEALED ACCESSIBLE POSITION.	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	CLEVERTRONICS LLIFE	A
E2	EXISTING NON MAINTAINED EMERGENCY LIGHT TO BE RETAINED				A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D8 - C90-E3.2.	WHITE	CLEVERTRONICS LUBPRO-SM	A
SIGN 1	RELOCATE THE EXISTING ETERNAL FLAME ILLUMINATED SIGN POWER SUPPLY POSITIONED AS PER THE ARCHITECTUAL ELEVATIONS.				C
SIGN 2	RELOCATE THE EXISTING ETERNAL LEST WE FORGET ILLUMINATED SIGN POWER SUPPLY POSITIONED AS PER THE ARCHITECTUAL ELEVATIONS.				C



C3365a - MAROOCHY RSL - SPORTS BAR REFURBISHMENT


C3365a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 28 MARCH 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
SIGN 3		PROVIDE A NEW ILLUMINATED ENTRY SIGN POWER SUPPLY UTILISING A NEW 20AMP RCBO PROTECTED CIRCUIT FROM DB-2A. UPGRADE THE DB-2A DYNALITE CONTROL SYSTEM TO SWITCH THE NEW ENTRY SIGN CIRCUIT. IT IS ACCEPTABLE TO UTILISE AN EXISTING DB-2A SIGN CIRCUIT AND CONTROL IF IT HAS APPROPRIATE CAPACITY AND IS CONFIGURED TO TURN THE SIGN ON WHEN THE CLUB IS OPERATIONAL. POSITION THE POWER SUPPLY AS PER THE ARCHITECTURAL ELEVATION.			C
SIGN 4		PROVIDE A NEW ILLUMINATED ENTRY SIGN POWER SUPPLY UTILISING THE SIGN 3 POWER SUPPLY. POSITION THE POWER SUPPLY AS PER THE ARCHITECTURAL ELEVATION.			C
EARLY WARNING CIE (EWCIE)		EXISTING AS1670 COMPLAINT EARLY WARNING CONTROL AND INDICATING EQUIPMENT TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE CHANGES AND ADDITIONS TO THE EARLY WARNING SYSTEM			A
FIRE DETECTION CIE (FDCIE)		EXISTING AS1670 COMPLAINT FIRE DETECTION CONTROL AND INDICATING EQUIPMENT TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE CHANGES AND ADDITIONS TO THE FIRE DETECTION SYSTEM			A
FIRE EVACUATION SPEAKER		RECESSED 5W TWO-TONE 8-INCH CONE ALERT AND EVACUATION SPEAKER TO AS1670.1 C/W 100V MULTI-TAP TRANSFORMER AND FLUSH GRILLE PAINTED OUT TO MATCH THE CEILING.			A
SMOKE DETECTOR		SURFACE MOUNTED SMOKE DETECTOR TO AS1670. BK INDICATES THE DETECTOR IS TO BE PROVIDED AS BLACK.			A
THERMAL DETECTOR		SURFACE MOUNTED THERMAL DETECTOR TO AS1670.			A
LIGHTING CONTROL SWITCH PANEL (SPx)		6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	ALUMINIUM	DYNALITE ANTUMBRA DISPLAY	A
TWO-WAY LIGHT SWITCH		TWO-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1100mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL 2000 SERIES 30USM	B
CHANNEL x		CONTROL CHANNEL WITH A NUMERICAL REFERENCE. REFER TO THE POWER AND LIGHTING CONTROL SCHEMATIC / SCHEDULE			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO A PATCH PANEL IN COMMUNICATIONS CABINET CR-A VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL U.N.O	WHITE	CLIPSAL C2000 SERIES	A



C3365a - MAROOCHY RSL - SPORTS BAR REFURBISHMENT

C3365a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 28 MARCH 2025

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
TAB OUTLET		RJ45 CAT-6 TAB OUTLET, CABLED BACK TO A MULTI GANG OUTLET UNDER THE TAB COUNTER VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 6 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET.	WHITE	CLIPSAL C2000 SERIES	A
HDM1 OUTLET (A1)		PROVIDE EACH A1 POINT AS A FACTORY TERMINATED HDMI CABLE LESS THAN 15M IN LENGTH RUNNING BACK TO THE A2 HDMI POINT UNDER THE TAB COUNTER. PROVIDE SLACK IN THE CABLE AT EACH END TO ALLOW CONNECTION TO THE TV AND NODI. PERMANENTLY LABEL EACH OUTLET AND THE CABLES CORRESPONDING END. PROVIDE A WHITE TRADER COBRUSH FACEPLATE AT EACH HDMI POINT TO FACILITATE THE HDMI CABLES ENTERING THE WALL CAVITY.			A
HDM1 POINT (A2)		PROVIDE THE A2 POINT UNDER THE TAB COUNTER AS THE DESTINATION FOR THE A1 HDMI CABLES . PROVIDE SLACK IN THE CABLE AT EACH END TO ALLOW CONNECTION TO THE TV AND NODI. PERMANENTLY LABEL EACH OUTLET AND THE CABLES CORRESPONDING END. PROVIDE A WHITE TRADER COBRUSH FACEPLATE AT EACH HDMI POINT TO FACILITATE THE HDMI CABLES ENTERING THE WALL CAVITY.			A
COMMUNICATIONS RACK (CR-A)		EXISTING COMMUNICATIONS RACK TO BE UPGRADED AS NECESSARY INCLUDING NEW PATCH PANELS TO ACCOMMODATE THE ADDITIONAL COMMUNICATIONS OUTLETS. ALL EXISTING CABLING MADE REDUNDANT BY THE WORKS IS TO BE REMOVED. THE NEW PATCH PANELS AND PORT NUMBERING IS TO MATCH THE EXISTING.			A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET (USB)		DOUBLE POWER OUTLET C/W USB A AND USB C CHARGER POINTS AND CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT ABOVE BENCH AS PER THE ARCHITECTURAL DETAILS. RATING 10A U.N.O.	WHITE	LEGRAND EMUSB2PSA	C
DB-2A		EXISTING DISTRIBUTION BOARD DB-2A TO BE PROVIDED WITH A NEW 3 PHASE MCB TO SUPPLY DB-2C. THE EXISTING SWITCHGEAR MADE REDUNDANT BY THE WORKS IS TO BE REMOVED. UPDATE THE SCHEDULE AT PRACTICAL COMPLETION			A
DB-2C		NEW DISTRIBUTION BOARD DB-2C TO BE PROVIDED AS PER THE DB-2C SCHEDULE AND NOTES.			A