

1115SM VIXO SM



SPECIFICATIONS:

1.5 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	Rot 355°	Tilt 90°	Class I	IP54		Oval Beam Available	5 Year warranty	Made in Australia
--------	----------------------	---------------	----------	----------	---------	------	--	---------------------	-----------------	-------------------

CONSTRUCTION & DESIGN

- Surface mounted LED adjustable spotlight
- Constructed in pressure die cast aluminium alloy and finished in durable polyester powder-coat paint
- Available with circular or rectangular surface mount base (refer to dimming option table)
- Robust and versatile luminaire gives the flexibility for accent lighting or wide-area illumination
- Fully adjustable design with 355° rotation and 90° tilt
- Clear tempered glass, silicone seals and cable gland providing IP54 protection

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient thermal management provides premium optical and thermal performance
- Efficient optical control in various beam angles with no harsh cut off and ultra low glare
- Compatible with an Oval Beam Lens (Datasheet Available upon Request)

ELECTRICAL SYSTEM

- Supplied standard with an integral driver and terminal block (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ and Green Wall LED is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE - COLOUR CODE

Example: 1115SM-SP-3K-13W-03 or 1115SM-SP-3K-13W/R/DALI-03

SYSTEM POWER	COLOUR TEMP.	24° SP	36° FL	55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				SP	FL	VWFL
13W	3K	1115SM-SP-3K-13W	1115SM-FL-3K-13W	1115SM-VWFL-3K-13W	1589	1362	1370	1337
	4K	1115SM-SP-4K-13W	1115SM-FL-4K-13W	1115SM-VWFL-4K-13W	1760	1524	1531	1451
	5K	1115SM-SP-5K-13W	1115SM-FL-5K-13W	1115SM-VWFL-5K-13W	1578	1365	1376	1300
22W	3K	1115SM-SP-3K-22W	1115SM-FL-3K-22W	1115SM-VWFL-3K-22W	2533	2121	2133	2065
	4K	1115SM-SP-4K-22W	1115SM-FL-4K-22W	1115SM-VWFL-4K-22W	2814	2379	2389	2252
	5K	1115SM-SP-5K-22W	1115SM-FL-5K-22W	1115SM-VWFL-5K-22W	2519	2123	2139	2023

DIM CODE	OPTIONS	13W	22W
With circular surface mount base (Ø75x25mm)			
	Leading & Trailing edge	Std	Std
With rectangular surface mount base (170x95x40mm)			
/R/DALI	Dali Dimming / Switch Dim	✓	✓
/R/DSI	Digital Dimming	✓	✓
/R/AD	Analogue Dimming 1-10V	✓	✓
/R/DIM	Leading & Trailing edge	✓	✓

COLOUR CODE	
-03	Texture White
-07	Texture Black
-11	Texture Silver

