

1311

STORM



SPECIFICATIONS:

2.0 kg	CRI 82+	Class I	IK09	IP65		5 Year warranty	Made in Australia
--------	---------	---------	------	------	--	--------------------	-------------------

CONSTRUCTION & DESIGN

- Surface Mount or suspended LED Weatherproof luminaire
- Housing constructed in grey self-extinguishing polycarbonate
- UV resistant clear/frosted polycarbonate reeded diffuser with high output controlled light distribution and low glare illumination
- Silicone gaskets and stainless steel diffuser clips provide IP65 weather protection
- Ideal for low mount applications
- Maintained Emergency option available in independent or DALI monitored

OPTICAL & THERMAL PERFORMANCE

- Efficient optical control with no harsh cut off and ultra low glare
- Diffused very wide light distribution

ELECTRICAL SYSTEM

- Supplied standard with an integral driver and terminal block (refer to dimming option table)
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 45W total system power consumption with overload and short circuit protection
- >75,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Available in 3K or 4K colour temperature with low colour shift over time

CODE ORDERING GUIDE: PRODUCT CODE / OPTION CODE / DIM CODE - COLOUR CODE

Example: 1311-3K-45W/EM-09 or 1311-3K-45W/EM/DALI-09

SYSTEM POWER	COLOUR TEMP.	118x107° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		118x107°
45W	3K	1311-3K-45W	5832	4586
	4K	1311-4K-45W	6138	4815

DIM CODE		45W
/DALI	Dali Dimming / Switch Dim	✓
/DSI	Digital Dimming	✓
/AD	Analogue Dimming 1-10V	x
/DIM	Leading & Trailing edge	x
	Non-dimmable	Std

MODEL OPTION

/EM	Maintained Emergency
/EMD	Maintained Emergency DALI

COLOUR CODE

-09	Grey
-----	------

