



DS-2CD2345G0P-I

Discontinued

4 MP Super Wide Angle Fixed Turret Network

- High quality imaging with 4 MP resolution
- 180°super wide field of view
- Efficient H.265+ compression technology
- Clear imaging against strong back light due to 120 dB true WDR t
- Distortion correction
- Robust structure design with full metal materials



Sales Inquiry

Available models:

DS-2CD2345G0P-I(1.68mm)

Specification

Resources

Accessories

Specification

• Camera

Lens

Illuminator

Video

Network

Image

Interface

Event

General

Approval

Camera

Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.028 Lux @ (F2.0, AGC ON) B&W: 0.0028 Lux @ (F2.0, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Slow Shutter	Yes
Wide Dynamic Range	120 dB
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 360°, tilt: 0° to 75°, rotate: 0° to 360°

Lens

Lens Type	Fixed lens, 1.68 mm
FOV	1.68 mm, horizontal FOV: 180° , vertical FOV: 101° , diagonal FOV: 180°

*Product performance is based on testing in a controlled environment. Your results may vary due to several external and environmental factors.

Resources

Technical documents

Quick Start Guide

User Manual

FAQ



Firmware

i For better user experience, we highly recommend you to update your device to the latest firmware asap.

Firmware_V5.6.821_230831

Network Camera-V5.6.821 Release Note-IPC_G1 230831

Applied to:

DS-2CD2345G0P-I(1.68mm)

Accessories



[DS-1271ZJ-130-TRL](#)

[Pendant Mount](#)

☐ Compare



[DS-1273ZJ-130-TRL](#)

[Wall mount](#)

☐ Compare



[DS-1273ZJ-130B-TRL](#)

[Wall mount](#)

☐ Compare



[DS-1275ZJ-SUS](#)

[Vertical pole mount](#)

☐ Compare



[DS-1276ZJ-SUS](#)

[Corner mount](#)

☐ Compare



[DS-1280ZJ-DM8](#)

[Junction box](#)

☐ Compare

[DS-1281ZJ-M](#)





[Inclined ceiling mount](#)



Compare



 [Contact Us](#)

 [Subscribe Newsletter](#)

