

WOMBAT

Description

Architectural, surface mounted spotlight, ideally suited for highlighting a significant feature within either an indoor or outdoor setting. Available in various materials, colour temperatures beam angles and finishes, Wombat luminaire seamlessly fits in with other Nocturnal Lighting Ltd products to create the desired ambiance in any display environment.



Technical

LED type	Bridgelux® Gen7 V8 Array	Control gear	Remote
Rated power	9W	Dimming protocols	Dali, 0-10V, Phase Dim, On/Off
CRI	>80	Cable length	300 mm
Beam angles	Nominated in table below	Mounting options	Surface / Spike
Input power/Forward voltage	500mA / 18V DC	Weight	0.8 kg
Nominal lumens	790lm	Hardware	Glass lens, Gland, Cable
IP rating	IP65	Construction	Machined metal, heatsink
Colour temperature	2700K / 3000K / 4000K	Warranty	Two years

Product Generator

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessories
NL-1606CC	AB Aged brass	N Narrow	27 2700K	SM Surface	9W / 500mA	1 Dali	1 Honeycomb louver
	BR Brushed brass	M Medium	30 3000K			2 0-10V	2 Diffuser lens
	PB Black	W Wide	40 4000K			3 Phase	3 Spike mount
	PB White	EL Elliptical				4 On/Off	4 Spread lens
	CC Custom						

Order Number - example NL-1606CV-BR-M-30-SM-9W-1-3

NL-1606CC	-	-	-	-	SM	-	9W	-	-	-
-----------	---	---	---	---	----	---	----	---	---	---