

1002

KHO



SPECIFICATIONS:



CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Trim and housing constructed in steel and finished in durable polyester powder-coat paint
- Recessed black housing with a deep recessed light source creating a dynamic visual impact with ultra low glare lighting performance

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with a deep recessed light source and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with a quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE


- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1002-3K-8W-01 or 1002-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	40° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		40°
8W	3K	1002-3K-8W	914	420
	4K	1002-4K-8W	947	435
	5K	1002-5K-8W	851	395
13W	3K	1002-3K-13W	1589	688
	4K	1002-4K-13W	1760	769
	5K	1002-5K-13W	1578	692



DIM CODE	OPTIONS	8W	13W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
/DIM	Leading & Trailing edge	Std	Std

COLOUR CODE	
-01	Satin White

OVERALL VIEW

