

1374

RODAR



SPECIFICATIONS:

0.9 kg	82+ 3K and 4K	70+ 5K	Class I	IP54	CE	5 Year warranty	Made in Australia
--------	------------------	-----------	---------	------	----	--------------------	-------------------

CONSTRUCTION & DESIGN

- Surface mounted exterior downlight
- Constructed from aluminium alloy and finished in durable polyester powder-coat paint
- Clear tempered glass cover with silicone seals, providing IP54 protection

OPTICAL & THERMAL PERFORMANCE

- Efficient optics and integral heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied with an integral leading and trailing edge mains dimmable driver and terminal block
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE




- 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request

CODE ORDERING GUIDE:

PRODUCT CODE

COLOUR CODE

Example: 1374-SP-3K-13W-12

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT		
		PRODUCT CODE				SP	FL	VWFL
13W	3K	1374-SP-3K-13W	1374-FL-3K-13W	1374-VWFL-3K-13W	1589	1427	1432	1415
	4K	1374-SP-4K-13W	1374-FL-4K-13W	1374-VWFL-4K-13W	1760	1592	1597	1579
	5K	1374-SP-5K-13W	1374-FL-5K-13W	1374-VWFL-5K-13W	1578	1432	1442	1419

COLOUR CODE

-03




Textured White

-12



Dark Grey



Ø108

