

1345

ALTUS

1346



UNIQUE SQUARE
DOUBLE BATWING
LIGHT OUTPUT

SPECIFICATIONS:



6.0 kg



3K and 4K



5K



Class I

IK08

IP65



5

Year warranty



Made in Australia

CONSTRUCTION & DESIGN

- LED exterior adjustable floodlight
- Constructed in pressure die cast and extruded aluminium alloy and finished in durable polyester powdercoat paint
- Secure tilt adjustable mechanism for reliable and accurate alignment
- Tempered glass cover, stainless steel exposed fasteners and silicone seals provide IP65 weather protection

OPTICAL & THERMAL PERFORMANCE

- Unique square double batwing light output
- LED thermal management system incorporates both conduction and natural convection to transfer heat rapidly away from LED source
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral non-dimmable driver and 200mm input cable
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE


- 90W or 120W total system power consumption with overload and short circuit protection
- >150,000+ hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time


CODE ORDERING GUIDE:

PRODUCT CODE

COLOUR CODE

Example: 1345-3K-90W-03

SYSTEM POWER	COLOUR TEMP.	 65x65° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		65x65°
90W	3K	1345-3K-90W	11748	9651
	4K	1345-4K-90W	12342	10133
	5K	1345-5K-90W	11988	9843
120W	3K	1346-3K-120W	15210	11849
	4K	1346-4K-120W	16020	12441
	5K	1346-5K-120W	15560	12085



DIM CODE		90W	120W
/DALI	Dali Dimming / Switch Dim	✓	x
/DSI	Digital Dimming	x	x
/AD	Analogue Dimming 1-10V	x	x
/DIM	Leading & Trailing edge	Std	x
	Non-dimmable	x	Std

COLOUR CODE

-03

 Textured White

-07

 Textured Black

-11

 Textured Silver

SECURE TILT ADJUSTABLE
MECHANISM FOR RELIABLE
AND ACCURATE ALIGNMENT

