

884501SM

Phantom SM



CONSTRUCTION & DESIGN


- Surface mounted LED panel light with integral driver
- Constructed in aluminium and finished in satin white powdercoat paint
- Delivering superior light control compared to the highest performance T5 technology
- Sealed light engine and polycarbonate diffuser requires no maintenance providing IP54 protection
- Ideal applications in office lighting, break out spaces, corridors, schools, universities, shopping centres, retail outlets and commercial interiors

TECHNICAL PERFORMANCE

- 40W total system power consumption with overload and short circuit protection
- >50,000 hours lifespan (L70)
- Premium quality Japanese LED Module with high lumen output per watt
- Available in 4000K colour temperature with low colour shift over time

ELECTRICAL SYSTEM

- Supplied completely with integral dimmable driver
- All drivers come with power cord and plug
- Quick connect driver
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz



Weight (kg)	4000K								
4.0	CRI >80								

TOTAL SYSTEM POWER CONSUMPTION = 40W

WATTAGE	COLOUR TEMPERATURE		HOT LED LUMENS
40W	4000K	884501-4K	3084

SUPPLIED AS STANDARD WITH REMOTE NON-DIMMABLE DRIVER

TRIM COLOUR OPTIONS: ADD SUFFIX AFTER THE CODE

-01 Satin White