

1411

CORBEL



SPECIFICATIONS:

0.6 kg	82+ 3K and 4K	70+ 5K	125	Tilt 35°	SELV	IP54	CE	Available	5 Year warranty	Made in Australia
--------	------------------	-----------	-----	----------	------	------	----	-----------	--------------------	-------------------

CONSTRUCTION & DESIGN

- Recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- Low profile adjustable LED downlight with high lumen output
- Clear tempered glass front

OPTICAL & THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Efficient optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with a quick connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE


- 8W, 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1411-3K-8W-01 or 1411-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	55° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		55°
8W	3K	1411-3K-8W	828	620
	4K	1411-4K-8W	870	653
	5K	1411-5K-8W	888	639
13W	3K	1411-3K-13W	1519	1110
	4K	1411-4K-13W	1607	1168
	5K	1411-5K-13W	1646	1140
22W	3K	1411-3K-22W	2414	1766
	4K	1411-4K-22W	2584	1859
	5K	1411-5K-22W	2618	1813



OVERALL VIEW

DIM CODE		8W	13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
	Leading & Trailing edge	Std	Std	Std

COLOUR CODE	
-01	Satin White
-06	Matte Black

