

ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2931a - VICTORIA POINT SHARKS SPORTING CLUB					C2931a-0002(A).xls
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION A - 14 JULY 2023					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	3000K LED	REAR BAR RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION RHO 1001-3K-13W	A
L2	3000K LED	BAR COUNTER RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION RHO 1001-3K-13W	A
L3	3000K LED	AMENITY RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-3K-13W	A
L4	3000K LED	KIDS ROOM RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION COBALT 1400-3K-22W	A
L5	3000K LED	GAMING RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION RHO 1001-3K-13W	A
L6	3000K LED	RECEPTION CIRCULATION RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION COBALT 1402-3K-22W	A
L7	3000K LED	EXTERNAL ENTRY RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION COBALT 1402-3K-22W	A
L8	3000K LED	PORTE COCHERE RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION COBALT 1442-3K-28W	A
L9	4000K LED	OFFICE RECESSED DOWNLIGHT C/W REMOTE NON DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION ATRIA 1192-4K-22W	A
PL1	300 LUMEN +/- 10% 3000K E27 240 VOLT LED	300 DIA PENDANT LIGHT SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	NATURAL	LIGHT CO TAN TAN LIGHT SMALL	A
PL2	300 LUMEN +/- 10% 3000K E27 240 VOLT LED	600 DIA PENDANT LIGHT SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	NATURAL	LIGHT CO TAN TAN LIGHT MEDIUM	A
PL3	300 LUMEN +/- 10% 3000K E27 240 VOLT LED	900 DIA PENDANT LIGHT SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	NATURAL	LIGHT CO TAN TAN LIGHT LARGE	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2931a - VICTORIA POINT SHARKS SPORTING CLUB					C2931a-0002(A).xls
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION A - 14 JULY 2023					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
PL4	3000K LED	CUSTOM PENDANT WITH RING CANOPY IN 4 SECTIONS (2040MM DIA X 240MM WIDE) WHITE POWDER COAT FINISH WITH 36 X SUSPENSIONS BUBBLE 120MM, 4W PENDANT IN SMOKE GLASS (TBC), BLACK SUSPENSION CABLE UP TO 2M (L) REMOTE DALI DIMMABLE DRIVER ALLOW TO ASSEMBLE AND INSTALL. CONFIRM THE SUSPENSION HEIGHTS ON SITE WITH THE ARCHITECT. ALLOW A PC SUM FOR THE SUPPLY OF THE P4 FITTING.	TBA	ALLOW A PC SUM OF \$20,000.00 TO SUPPLY.	A
W1	3000K LED	134 DIA X 82 HIGH WALL LIGHT C/W REMOTE DALI DIMMABLE DRIVER. CONFIRM THE MOUNTING HEIGHT ON SITE WITH THE ARCHITECT.	WHITE GLASS BLACK ANODISED BACKPLATE	CREATIVE LIGHTING RIPPLE WALL LIGHT	A
W2	3000K LED	250 DIA WALL LIGHT C/W 120 DIA GLOBE AND A REMOTE DALI DIMMABLE DRIVER. CONFIRM THE MOUNTING HEIGHT ON SITE WITH THE ARCHITECT.	BUBBLE SOFT RETURN CERAMIC	LUMEN 8 BUBBLE SOFT RETURN CERAMIC WALL LIGHT	A
W3	3000K LED	EXTERNAL WALL MOUNTED DOWN LIGHT C/W INTEGRAL DALI DIMMABLE DRIVER	GRAPHITE	BEGA 24435	A
S1	WARM WHITE LED	HORIZONTAL LED STRIP WITHIN AN FLUSH RECESSED ALUMINIUM EXTRUSION MOUNTED WITHIN THE TAB COUNTER AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-12V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	A
S2	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED IN PLACE WITHIN THE RECEPTION FEATURE WALL AS PER THE DETAILED ELEVATION AND THE ARCHITECTURAL DETAIL PROVIDE THE S2 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S3	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED IN PLACE BEHIND THE MIRROR AS PER THE ARCHITECTURAL DETAIL PROVIDE A REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S4	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED INTO THE BAR BULKHEAD AS PER THE ARCHITECTURAL DETAIL PROVIDE THE S4 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A



ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2931a - VICTORIA POINT SHARKS SPORTING CLUB		C2931a-0002(A).xls			
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION A - 14 JULY 2023					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S5	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED IN PLACE IN THE BAR FACE SKIRTING AS PER THE ARCHITECTURAL DETAIL PROVIDE THE S5 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S6	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED IN PLACE IN THE BAR FACE SKIRTING AS PER THE ARCHITECTURAL DETAIL PROVIDE THE S6 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S7	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED IN PLACE UNDER THE BAR COUNTER TOP AS PER THE ARCHITECTURAL DETAIL PROVIDE THE S7 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER GROUP NOT EXCEEDING 10M OF STRIP	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A
S8	WARM WHITE LED	HORIZONTAL LED STRIP UP LIGHT WITHIN AN FLUSH RECESSED ALUMINIUM EXTRUSION MOUNTED WITHIN THE REAR COUNTER DISPLAY AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L8 STRIP WITH A COMMON REMOTE DEDICATED 240-12V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT PER 20M OF STRIP	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D63 - C90-D63.	WHITE	CLEVERTRONICS LLIFE	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2	BLACK	CLEVERTRONICS LUBPRO-SM	A
ONE-WAY LIGHT SWITCH		ONE-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A
TWO-WAY LIGHT SWITCH		TWO-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A



ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2931a - VICTORIA POINT SHARKS SPORTING CLUB		C2931a-0002(A).xls			
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION A - 14 JULY 2023					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
LIGHTING CONTROL SWITCH PANEL (SPx)		6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	ALUMINIUM	DYNALITE ANTUMBRA DISPLAY	A
HAND DRYER CONNECTION (HD)		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND FOR THE HAND DRYER MOUNT THE GPO AS PER THE ARCHITECTURAL DETAIL	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SINGLE POWER OUTLET AUTO DOOR (AD)		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED CONCEALED WITHIN THE AUTO DOOR MULLION. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
SINGLE 15A POWER OUTLET SUSPENDED (SUS)		SINGLE 15A POWER OUTLET SUSPENDED TO 1600 AFFL UNLESS NOTED OTHERWISE VIA A 3MM STAINLESS STEEL WIRE ROPE.	WHITE	CLIPSAL "56 SERIES" 56SPO315	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SPECIAL PURPOSE OUTLET		SPECIAL PURPOSE OUTLET TYPE AS NOTED. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.			A
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	A
SIGN CONNECTION		COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE GPO / ISOLATORS ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW.			A
DB-B		DISTRIBUTION BOARD DB-B AS PER THE DB-B SCHEDULE. COLOUR GREY HINGED ESCUTCHEON C/W 1/4 TURN LATCHES AND D HANDLES. PROVIDE A SHOP DRAWING OF DB-B FOR APPROVAL.			A
DB-C		DISTRIBUTION BOARD DB-C AS PER THE DB-C SCHEDULE. COLOUR GREY HINGED ESCUTCHEON C/W 1/4 TURN LATCHES AND D HANDLES. PROVIDE A SHOP DRAWING OF DB-B FOR APPROVAL.			A
MSB		MAIN SWITCHBOARD TO BE PROVIDED WITH NEW CIRCUIT BREAKERS TO SUPPLY DB-B AND DB-C. UPDATE THE LABELLING AT PRACTICAL COMPLETION.			A



ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2931a - VICTORIA POINT SHARKS SPORTING CLUB		C2931a-0002(A).xls			
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION A - 14 JULY 2023					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
COMMUNICATIONS RACK (CR-A)		IT FREE STANDING 42 RU MINIMUM 800 DEEP 800 WIDE COMMUNICATIONS RACK CR-A PROVIDE A SHOP DRAWING OF THE RACK INCLUDING THE ARRANGEMENT OF EQUIPMENT PROVIDED WITHIN IT AS PART OF THE CONTRACT FOR APPROVAL. PROVIDE THE RACK WITH THE REQUIRED CAT 6 PATCH PANELS, CABLE MANAGEMENT AS PER THE SPECIFICATION. PROVIDE THE RACK WITH CASTERS.		4 CABLING SKU 002.001.4280	A
COMMUNICATIONS RACK (CR-B)		GAMING FREE STANDING 42 RU MINIMUM 600 DEEP 600 WIDE COMMUNICATIONS RACK CR-B PROVIDE A SHOP DRAWING OF THE RACK INCLUDING THE ARRANGEMENT OF EQUIPMENT PROVIDED WITHIN IT AS PART OF THE CONTRACT FOR APPROVAL. PROVIDE THE RACK WITH THE REQUIRED CAT 6 PATCH PANELS, CABLE MANAGEMENT AS PER THE SPECIFICATION. PROVIDE THE RACK WITH CASTERS.		4 CABLING SKU 002.001.4280	A
COMMUNICATIONS RACK (CR-C)		PROVIDE A FREE STANDING 42 RU MINIMUM 600 DEEP 600 WIDE RACK CR-C FOR THE SECURITY / AC CONTRACTORS TO USE. PROVIDE A SHOP DRAWING OF THE RACK. PROVIDE THE RACK WITH CASTERS.		4 CABLING SKU 002.001.4280	A
TAB COMMUNICATIONS RACK (CR-T)		PROVIDE THE TAB COMMUNICATIONS RACK CR-T AS A 600 WIDE X 600 DEEP 12RU 19 INCH RACK C/W CASTERS SOLID SIDES NO REAR COVER OR FRONT DOOR. ENSURE THE CABLING ENTERING THE RACK IS LOOPED WITH SUFFICIENT LENGTH TO ALLOW THE RACK TO BE WITHDRAWN FROM UNDER THE COUNTER. SUBMIT DETAILS OF THE RACK FOR APPROVAL.			A
COMMUNICATIONS OUTLET T		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 PATCH PANELS IN RACK CR-T VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 PATCH PANELS IN RACK CR-1 VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
CAT 6 GAMING OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 DEDICATED GAMING PATCH PANELS IN RACK CR-2 VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
GAMING FIBRE (GF)		INSTALL DUPLEX FIBRE OPTIC CABLE BETWEEN THE POKER MACHINE BASES AND FROM THE POKER MACHINE BASES BACK TO RACK CR-2 AS INDICATED. THE DUPLEX FIBRE OPTIC CABLE WILL BE SUPPLIED AND TERMINATED BY OTHERS.			A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2931a - VICTORIA POINT SHARKS SPORTING CLUB		C2931a-0002(A).xls			
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION A - 14 JULY 2023					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
HDMI CABLE (HDM1)		PROVIDE EACH HDMI POINT AS A FACTORY TERMINATED HDMI CABLE LESS THAN 15M IN LENGTH RUNNING BACK TO THE NOMINATED HDMI POINT ADJACENT THE NODI LOCATED IN JOINERY. PROVIDE SLACK IN THE CABLE AT EACH END TO ALLOW CONNECTION TO THE TV AND NODI. PERMANENTLY LABEL EACH OUTLET AND THE CABLES CORRESPONDING END. PROVIDE A WHITE TRADER COBRUSH FACEPLATE AT EACH HDMI POINT TO FACILITATE THE HDMI CABLES ENTERING THE WALL CAVITY.			A
SECURITY EQUIPMENT		EXISTING FIRE INDICATOR PANEL TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE WORKS. RETAIN THE EXISTING 240 VOLT POWER SUPPLY.			A
ELECTRICAL SERVICES POLE (SV)		PROVIDE EACH ELECTRICAL SERVICES POLE AS A ROUND (LESS THAN 100MM DIA) TWO CHANNEL POWDER COATED POLE FROM THE GAMING BASE TO THE CEILING TO PROVIDE POWER AND COMMUNICATIONS CABLING ACCESS FROM THE CEILING TO THE GAMING MACHINE BASE. PROVIDE A FLANGE AROUND THE POLE TO CONNECT IT TO THE BASE AND TO THE CEILING. THE ARCHITECT WILL CONFIRM THE COLOUR. (ALLOW FOR DULUX BRIGHT GOLD PEARL MATT 9717420Q IN COLOUR) SUBMIT DETAILS OF THE PROPOSED POLE FOR APPROVAL.			A
FIRE INDICATOR PANEL (FIP)		EXISTING FIRE INDICATOR PANEL TO BE UPGRADED AS NECESSARY TO ACCOMMODATE THE WORKS. RETAIN THE EXISTING 240 VOLT POWER SUPPLY.			A
FIRE EVACUATION SPEAKER		RECESSED 5W TWO-TONE 8-INCH CONE ALERT AND EVACUATION SPEAKER TO AS1670.1 C/W 100V MULTI-TAP TRANSFORMER AND FLUSH GRILLE PAINTED OUT TO MATCH THE CEILING. (SM) DENOTES TO BE SURFACE MOUNT			A
SMOKE DETECTOR		SURFACE MOUNTED SMOKE DETECTOR TO AS1670. WHITE			A
VISUAL ALARM		FIRE ALARM STROBE LIGHT AS PER AS1670.1			A
FIRE ALARM SYSTEM DOOR INTERFACE		INTERFACE THE FIRE ALARM SYSTEM TO THE DOOR CONTROL SYSTEM SUCH THAT THE DOOR IS UNLOCKED VIA A FAIL SAFE SIGNAL UPON ALARM.			A