


1400

## COBALT 105



## SPECIFICATIONS:



## CONSTRUCTION &amp; DESIGN

- Recessed LED fixed downlight available in six sizes
- Constructed in die cast aluminium alloy and finished in durable polyester powdercoat paint
- Low profile fixed LED downlight with high lumen output and low glare
- Clear tempered glass

## OPTICAL &amp; THERMAL PERFORMANCE

- Reflector, diffuser and efficient heatsink provides premium optical and thermal performance
- Efficient optical control in wide beam angle and no harsh cut off and ultra low glare

## ELECTRICAL SYSTEM

- Supplied standard with a remote leading and trailing edge mains dimmable driver, which is compatible with a range of dimming systems
- All drivers come with a quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE

- 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

## CODE ORDERING GUIDE:

PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1400-3K-13W-01 or 1400-3K-13W/DALI-01

SYSTEM POWER	COLOUR TEMP.	47° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		47°
13W	3K	1400-3K-13W	1519	1070
	4K	1400-4K-13W	1607	1126
	5K	1400-5K-13W	1558	1099
22W	3K	1400-3K-22W	2414	1666
	4K	1400-4K-22W	2584	1754
	5K	1400-5K-22W	2506	1711

DIM CODE		13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
	Leading & Trailing edge	Std	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black

