

ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2933a - ZILLMERE SPORTS CLUB - GAMING EXTENSION					C2933a-0002(C).xls
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION C - 05 MARCH 2024					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK					
www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	240VOLT 400LM +/- 10% 3000K LED	AMENITY 150DIA PENDANT TO BE SUSPENDED WITH THE CORD HEIGHT ADJUSTED AS DIRECTED BY THE ARCHITECT ON SITE	SEMI BLACK TRANSPARENT GOLD CORD	LIGHTING COLLECTIVE SCANDINAVIAN HANGING LED GLOBW MOON PENDANT MEDIUM	C
L2	240VOLT 200LM +/- 10% 3000K LED	AMENITY ENTRY 120 DIA WALL LIGHT ALLOW TO INSTALL AS PER THE ARCHITECTURAL ELEVATION	BRASS BODY OPAL GLASS	ABOUTSPACE CATERPILLAR WALL A LED INDOOR WALL LIGHT	C
L3	240VOLT 800LM +/- 10% 3000K LED	RECEPTION PENDANT TO BE SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	WHITE	ABOUTSPACE CAROLINE PENDANT	C
L4	240VOLT 400LM +/- 10% 3000K LED	CASHIER WALL LIGHT 200 DIA ALLOW TO INSTALL AS PER THE ARCHITECTURAL ELEVATION	SLIK BRASS	ABOUTSPACE GOSSA WALL LIGHT	C
L5	2 X 6W 3000K LED	ENTRY IP65 WALL LIGHT 110 DIA X 200 HIGH ALLOW TO INSTALL AS PER THE ARCHITECTURAL ELEVATION	CONCRETE / SANDSTONE	ABOUT SPACE MONOLITH	C
L6	240VOLT 200LM +/- 10% 3000K LED	AMENITY 125 DIA PENDANT TO BE SUSPENDED WITH THE CORD HEIGHT ADJUSTED AS DIRECTED BY THE ARCHITECT ON SITE	SEMI BLACK TRANSPARENT GOLD CORD	LIGHTING COLLECTIVE SCANDINAVIAN HANGING LED GLOBW MOON PENDANT SMALL	C
L7	240VOLT 400LM +/- 10% 3000K LED	CASHIER PENDANT 250 DIA X 405 HIGH TO BE SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	CHAMPAGNE BRASS DROP	ABOUT SPACE CAMILLA GLASS RIBBED PENDANT	C
L8A	240VOLT 400LM +/- 10% 3000K LED	SPORTS BAR WALL PENDANT 300DIA 500 HIGH ALLOW TO INSTALL AS PER THE ARCHITECTURAL DETAIL	WHITE FABRIC	ABOUT SPACE SIRIUS PENDANT	C
L8B	240VOLT 400LM +/- 10% 3000K LED	SPORTS BAR WALL PENDANT 350DIA 500 HIGH ALLOW TO INSTALL AS PER THE ARCHITECTURAL DETAIL	WHITE FABRIC	ABOUT SPACE NEPTUNE PENDANT	C
L9	400 LM +/- 10% 3000K LED	130 DIA GAMING PENDANT C/W REMOTE DALI DIMMABLE DRIVER PER FIVE FITTINGS TO BE SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	BRASS BODY AND DROP	ABOUT SPACE AMENDO MINI	C
L10	400 LM +/- 10% 3000K LED	130 DIA GAMING PERFORATED PENDANT C/W REMOTE DALI DIMMABLE DRIVER PER FIVE FITTINGS TO BE SUSPENDED AS DIRECTED BY THE ARCHITECT ON SITE	PERFORATED BRASS BODY AND DROP	ABOUT SPACE AMENDO MINI PERFORATED	C



ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2933a - ZILLMERE SPORTS CLUB - GAMING EXTENSION					C2933a-0002(C).xls
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION C - 05 MARCH 2024					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L11	34W 4000K LED	600 X 600 LAY IN FLAT PLATE LED FITTING C/W REMOTE DRIVER MOUNTED IN A FLUSH RECESSED PB MOUNTING KIT	WHITE TRIM	GAMMA ILLUMINATION AXIS 1548-4K-34W C/W FLUSH RECESS PB KIT	A
L12	13W 3000K LED	AMENITY ENTRY RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-3K-13W	A
L13	28W 3000K LED	GAMING RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION CORBAL 1418-3K-28W	A
L14	240VOLT 400LM +/- 10% 3000K LED	RECEPTION WALL LIGHT 480 HIGH X 245 DEEP WALL MOUNTED AS PER THE ARCHITECTURAL ELEVATION	BRASS BODY OPAL GLASS	ABOUT SPACE DANTE LED 120 DIA GLASS	C
L15	8W 3000K LED	AMENITY RECESSED DOWNLIGHT C/W REMOTE DRIVER	WHITE	GAMMA ILLUMINATION MYLO 1004-3K-8W	A
L16	13W 3000K LED	GENERAL RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION CORBAL 1410-3K-13W	A
L17	22W 3000K LED	RECEPTION RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION COBALT 1402-3K-22W	A
L18	28W 3000K LED	ENTRY RECESSED DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	GAMMA ILLUMINATION COBALT 1442-3K-28W	A
L19	WARM WHITE LED	TWO HORIZONTAL LED STRIPS WITHIN AN FLUSH RECESSED ALUMINIUM EXTRUSION MOUNTED WITHIN THE REAR CASHIER SHELIVING AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-12V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	A
L20	NO LONGER REQUIRED				B
L21	12W/M 3000K LED	FLEXIBLE LED ROPE FLEX SCREW FIXED RECESSED INTO THE BAR SKIRTING AS PER THE ARCHITECTURAL DETAIL PROVIDE THE L21 STRIP WITH A COMMON REMOTE 240-24V POWER SUPPLY AND A DALI DIMMABLE INTERFACE UNIT	WHITE	NPA L-NF-GLOW-WW + POWER SUPPLY & DALI CONTROLLER	A



ELECTRICAL DESIGN GROUP


ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2933a - ZILLMERE SPORTS CLUB - GAMING EXTENSION				C2933a-0002(C).xls	
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION C - 05 MARCH 2024					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L22	45W 4000K LED	EXTERNAL WALL MOUNTED FLOOD LIGHT C/E INTEGRAL DRIVER	SILVER	GAMMA ILLUMINATION 1341-4K-45W	A
L23	WARM WHITE LED	TWO HORIZONTAL AND TWO VERTICAL LED STRIPS TO SURROUND THE MIRROR AS PER THE L23 ELEVATION RUN THE STRIP WITHIN AN FLUSH RECESSED ALUMINIUM EXTRUSION MOUNTED CONCEALED BEHIND THE MIRROR AS PER THE ARCHITECTURAL DETAIL PROVIDE THE STRIP WITH A REMOTE DEDICATED 240-12V POWER SUPPLY	NATURAL	NEON PRODUCTS AUSTRALIA LF-DFB-WW-300-12 + PR-LIN172153-F	B
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D63 - C90-D63.	WHITE	CLEVERTRONICS LLIFE	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2	BLACK	CLEVERTRONICS LUBPRO-SM	A
ONE-WAY LIGHT SWITCH		ONE-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES 30USM	A
LIGHTING CONTROL SWITCH PANEL (SPx)		6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	ALUMINIUM	DYNALITE ANTUMBRA DISPLAY	A
HAND DRYER CONNECTION (HD)		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND FOR THE HAND DRYER MOUNT THE GPO AS PER THE ARCHITECTURAL DETAIL	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SINGLE POWER OUTLET AUTO DOOR (AD)		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED CONCEALED WITHIN THE AUTO DOOR MULLION. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C2933a - ZILLMERE SPORTS CLUB - GAMING EXTENSION		C2933a-0002(C).xls			
ELECTRICAL EQUIPMENT SCHEDULE					
REVISION C - 05 MARCH 2024					
THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm					
TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	A
DB-A		DISTRIBUTION BOARD DB-A AS PER THE DB-A SCHEDULE. COLOUR GREY HINGED ESCUTCHEON C/W 1/4 TURN LATCHES AND D HANDLES. PROVIDE A SHOP DRAWING OF DB-A FOR APPROVAL. AS PER THE NOTES DB-A IS TO BE SUPPLIED FROM A NEW 160 AMP MCCB IN THE MSB VIA A NEW 4C 70mm SUBMAIN.			A
DB-B - P1		PROVIDE CIRCUIT DB-B - P1 A NEW 20 AMP SINGLE PHASE 2.5MM RCBO PROTECTED CIRCUIT FROM THE EXISTING MSB DISTRIBUTION BORD (DB-B)			A
DB-B		EXISTING MSB DISTRIBUTION BORD (DB-B)			A
MSB		EXISTING MSB TO BE UPGRADED TO ACCOMMODATE THE ADDITIONAL 160 AMP MCCB TO SUPPLY DB-A. UPDATE THE MSB LABELS AT PRACTICAL COMPLETION			A
COMMUNICATIONS RACK (CR-1)		EXISTING COMMUNICATIONS RACK CR-1 PROVIDE THE RACK WITH THE REQUIRED CAT 6 PATCH PANELS TO FACILITATE THE ADDITIONAL COMMUNICATIONS OUTLETS.			A
COMMUNICATIONS RACK (CR-2)		EXISTING COMMUNICATIONS RACK CR-2 PROVIDE THE RACK WITH THE REQUIRED CAT 6 PATCH PANELS TO FACILITATE THE ADDITIONAL GAMING OUTLETS.			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 PATCH PANELS IN RACK CR-1 VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
CAT 6 GAMING OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO CAT 6 DEDICATED GAMING PATCH PANELS IN RACK CR-2 VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL UNLESS NOTED OTHERWISE	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
GAMING FIBRE (GF)		INSTALL DUPLEX FIBRE OPTIC CABLE BETWEEN THE POKER MACHINE BASES AND FROM THE POKER MACHINE BASES BACK TO RACK CR-2 AS INDICATED. THE DUPLEX FIBRE OPTIC CABLE WILL BE SUPPLIED AND TERMINATED BY OTHERS.			A