


1450

JADE 200



SPECIFICATIONS:



0.4 kg



3K and 4K



5K



185



SELV



IP54



CE



Available



5 Year warranty



Made in Australia

CONSTRUCTION & DESIGN

- Recessed LED fixed downlight available in three sizes
- Constructed in aluminium and finished in durable polyester powdercoat paint
- Recessed acrylic diffuser gives a symmetrical wide beam distribution with high lumen output and providing IP54 protection

OPTICAL & THERMAL PERFORMANCE

- Reflector, diffuser and efficient heatsink provides premium optical and thermal performance
- Efficient optical control in wide beam angle and no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with a remote driver (refer to dimming option table)
- All drivers come with a quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 22W or 28W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time

CODE ORDERING GUIDE:


PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1450-3K-22W-01 or 1450-3K-22W/DALI-01

SYSTEM POWER	COLOUR TEMP.	90° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		90°
22W	3K	1450-3K-22W	2414	1754
	4K	1450-4K-22W	2584	1847
	5K	1450-5K-22W	2520	1809
28W	3K	1450-3K-28W	3213	2466
	4K	1450-4K-28W	3380	2596
	5K	1450-5K-28W	3309	2542

DIM CODE		22W	28W
/DALI	Dali Dimming / Switch Dim	✓	✓
/DSI	Digital Dimming	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓
/DIM	Leading & Trailing edge	Std	✓
	Non-dimmable	×	Std

COLOUR CODE	
-01	Satin White



80

200

