

1573

MOLO



UNIQUE SQUARE
DOUBLE BATWING
LIGHT OUTPUT

SPECIFICATIONS:

One way	6.1 kg	CRI 82+ 3K and 4K	CRI 70+ 5K	Class I	IP65	CE	5 Year warranty	Made in Australia
---------	--------	----------------------	---------------	---------	------	----	--------------------	-------------------

353

CONSTRUCTION & DESIGN

- Surface mounted LED exterior wall light for up and down illumination
- Housing constructed in pressure die cast aluminium alloy and finished in durable powdercoat paint
- Robust housing for superior durability
- Wall cable gland power entry
- Clear tempered glass cover, and silicone gaskets provides IP65 weather protection
- Can be used as up or downlight

OPTICAL & THERMAL PERFORMANCE

- LED thermal management incorporates both conduction and natural convection to transfer heat rapidly away from LED source to achieve maximum life of LED
- High efficiency optics for brilliant optical control with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral driver (refer to dimming options table)
- Power factor > 0.9 with active power factor correction
- Supplied with 200mm input cable
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 28W, 45W or 52W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (macAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time


CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1573-3K-28W-03 or 1573-3K-28W/DALI-03

SYSTEM POWER	COLOUR TEMP.	65x65° BEAM ANGLE	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT
		PRODUCT CODE		65x65°
28W	3K	1573-3K-28W	3427	2730
	4K	1573-4K-28W	3641	2894
	5K	1573-5K-28W	3540	2814
45W	3K	1573-3K-45W	5177	4142
	4K	1573-4K-45W	5569	4390
	5K	1573-5K-45W	5416	4270
52W	3K	1573-3K-52W	5936	4706
	4K	1573-4K-52W	6426	4989
	5K	1573-5K-52W	6249	4852

DIM CODE		28W	45W	52W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	x	x
/DIM	Leading & Trailing edge	Std	✓	x
	Non-dimmable	x	Std	Std

COLOUR CODE		
-03		Textured White
-07		Textured Black
-11		Textured Silver



ALTERNATIVE MOUNTING

