



TRADESTAR SE7169TC - 70/250W

A versatile LED floodlight range with five models ranging from 70 - 250 watt, now with selectable CCT.

Application






Perfect for any exterior space from residential small wattage designs through to high performance commercial applications

Design Specifications

- Integral LED control gear, non-dimmable 70, 100, 150, 200, 250 watt models
- Robust die-cast aluminium body profile with multi-function angled trunnion bracket, colour black
- Pre-wired with 1500mm UV rated flex for easy installation
- IK08, IP65 rated
- CRI >80, selectable CCT 3000/4000/5000K and an impressive 120lm/W optical performance at 4000K
- 100 degree wide beam distribution




Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI
	SE7169/70TC/BK	240	70	7350/8400/7700	3000/4000/5000	80
	SE7169/100TC/BK	240	100	10500/12000/11000	3000/4000/5000	80
	SE7169/150TC/BK	240	150	15750/18000/16500	3000/4000/5000	80
	SE7169/200TC/BK	240	200	21000/24000/22000	3000/4000/5000	80
	SE7169/250TC/BK	240	250	26250/30000/27500	3000/4000/5000	80

Beam Angle (°)	Body Colour	Dim (mm)	Mass (kg)
100	Black	210(L) x 54(W) x 220(H)	1.9
100	Black	240(L) x 70(W) x 250(H)	2.9
100	Black	270(L) x 76(W) x 300(H)	3.8
100	Black	310(L) x 81(W) x 340(H)	4.9
100	Black	360(L) x 92(W) x 400(H)	7.1

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Photometric Data

Photometric Data

Unit: cd C0/C180 — C90/C270 —

SE7169/70TC/BK at 5000K

SE7169/250TC/BK at 5000K

