



## RENMARK S9083R35TC/DP - 24/35W


24/35 watt LED downlight with selectable CCT and power, IP64

### Application

Ideal for any retail, residential or commercial interior space

### Design Specifications

- Premium aluminium body profile
- Stylish white body profile and WH trim with optional WH square, BK round or BK square quick connect plastic trims to order
- High performance faceted reflector profile, beam 60° , UGR <19
- Remote, non-dimmable flickerCONTROLLED LED driver, with flex and plug
- Selectable CCT 3000, 4000, 5700K
- IC - 4 rated, double insulated







### Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V DALI / DSI**



## Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	Beam Angle (°)
	S9083R35TC/DP	240	24/35	3000/3300/3150	3000/4000/5700	60
	S9083SQ/WH/P					
	S9083RD/BK/P					
	S9083SQ/BK/P					

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)	IPART
OPTIONAL	90	WHITE	195	232	110(H)	N/A
		WHITE	195		232(L) x 232(W)	N/A
		BLACK	195	232		N/A
		BLACK	195		232(L) x 232(W)	N/A

REES	VEET
N/A	N/A
N/A	N/A
N/A	N/A
N/A	N/A

NOTE: lumens (lm) displayed are at MAXIMUM power

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

## Dimensions

