

1004

MYLO



## SPECIFICATIONS:

0.3 kg	3K and 4K	5K	95	Tilt 30°	SELV	IP44	CE	Available	Oval Beam Available	5 Year warranty	Made in Australia
--------	-----------	----	----	----------	------	------	----	-----------	---------------------	-----------------	-------------------

## CONSTRUCTION &amp; DESIGN

- Low profile recessed LED adjustable downlight
- Constructed in die cast aluminium alloy and finished in durable polyester powder-coat paint
- Low profile adjustable LED downlight with up to 22W system power and high lumen output
- Clear tempered glass

## OPTICAL &amp; THERMAL PERFORMANCE

- Optics and efficient heatsink provides premium optical and thermal performance
- Thermodynamically compact efficient heatsink design
- Efficient optical control with no harsh cut off and ultra low glare
- Compatible with an Oval Beam Lens
- Complies thermally with IC-4 and IC-F classification in accordance with AS/NZS 60598 (8W and 13W product only)

## ELECTRICAL SYSTEM





- Supplied standard with a remote leading and trailing edge mains dimmable driver (refer to dimming options table)
- All drivers come with quick-connect harness, power cord and plug
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

## TECHNICAL PERFORMANCE

- 8W, 13W or 22W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with low colour shift over time
- CRI 90+ is available upon request


## CODE ORDERING GUIDE: PRODUCT CODE / DIM CODE - COLOUR CODE

Example: 1004-SP-3K-8W-01 or 1004-SP-3K-8W/DALI-01

SYSTEM POWER	COLOUR TEMP.	 24° SP	 36° FL	 47° WFL	 55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					SP	FL	WFL	VWFL
8W	3K	1004-SP-3K-8W	1004-FL-3K-8W	1004-WFL-3K-8W	-	914	848	857	850	-
	4K	1004-SP-4K-8W	1004-FL-4K-8W	1004-WFL-4K-8W	-	947	882	888	880	-
	5K	1004-SP-5K-8W	1004-FL-5K-8W	1004-WFL-5K-8W	-	851	800	805	797	-
13W	3K	1004-SP-3K-13W	1004-FL-3K-13W	-	1004-VWFL-3K-13W	1589	1391	1398	-	1361
	4K	1004-SP-4K-13W	1004-FL-4K-13W	-	1004-VWFL-4K-13W	1760	1557	1562	-	1477
	5K	1004-SP-5K-13W	1004-FL-5K-13W	-	1004-VWFL-5K-13W	1578	1394	1404	-	1323
22W	3K	1004-SP-3K-22W	1004-FL-3K-22W	-	1004-VWFL-3K-22W	2533	2167	2177	-	2102
	4K	1004-SP-4K-22W	1004-FL-4K-22W	-	1004-VWFL-4K-22W	2814	2430	2438	-	2292
	5K	1004-SP-5K-22W	1004-FL-5K-22W	-	1004-VWFL-5K-22W	2519	2169	2183	-	2059

DIM CODE	OPTIONS	8W	13W	22W
/DALI	Dali Dimming / Switch Dim	✓	✓	✓
/DSI	Digital Dimming	✓	✓	✓
/AD	Analogue Dimming 1-10V	✓	✓	✓
/DIM	Leading & Trailing edge	Std	Std	Std

COLOUR CODE		
-01		Satin White
-06		Matte Black



## OVERALL VIEW

