



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3704a - EAGERS VW & CHERY, IPSWICH

C3704a-0002(A).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION A - 25 FEBRUARY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
D1C	35W 4000K LED	RECESSED DOWNLIGHT	BLACK	LUMIQUI CEA1401 II	A
D2C	24W 4000K LED	RECESSED DOWNLIGHT	BLACK	LUMIQUI CEA13501 II	A
LF1	PROVIDE POWER FOR THE SUSPENDED CEILING FEATURE LIGHT. COORDINATE THE CONNECTION POINT ON SITE WITH THE FEATURE SUPPLIER.				A
LF2	PROVIDE POWER FOR THE SUSPENDED CEILING FEATURE LIGHT. COORDINATE THE CONNECTION POINT ON SITE WITH THE FEATURE SUPPLIER.				A
D1	9W 3000K LED	RECESSED DOWNLIGHT	WHITE	LUMIQUI CEJ61075-S	A
D2	12W 2700K LED	RECESSED DOWNLIGHT	WHITE	LUMIQUI CEJ61075-S	A
D3	15W 4000K LED	RECESSED DOWNLIGHT	WHITE	LUMIQUI CEJ61075-S	A
D4A	24W 4000K LED	RECESSED SQUARE DOWNLIGHT	BLACK	LUMIQUI CES5031C	A
D5B	2 X 35W 4000K LED	RECESSED RECTANGLE DOWNLIGHT	BLACK	LUMIQUI CES5031C	A
D6	10 X 2W 3500K LED	RECESSED 285 X 50 LINEAR FITTING	WHITE	LUMIQUI CES8210M II	A
F2	31W 4000K LED	RECESSED 600 X 600 PANEL LIGHT	BLACK	LUMIQUI CEP6060G5	A
P2	40W 3500K LED	1204 LINEAR PENDANT	WHITE	LUMIQUI CXUD5575G	A
W2	28W 2700K LED	RECESSED 1202 X 36 LINEAR FITTING	BLACK	LUMIQUI CXR3030-12	A



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3704a - EAGERS VW & CHERY, IPSWICH

C3704a-0002(A).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION A - 25 FEBRUARY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
LL		PROVIDE POWER FOR THE SUSPENDED CEILING FEATURE LIGHT. COORDINATE THE CONNECTION POINT ON SITE WITH THE FEATURE SUPPLIER.			A
LP		PROVIDE POWER FOR THE SUSPENDED CEILING FEATURE LIGHT. COORDINATE THE CONNECTION POINT ON SITE WITH THE FEATURE SUPPLIER.			A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	CLEVERTRONICS CLIFE	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. PROVIDE A CUSTOM WHITE COUNTER LEAVER MOUNTING BRACKET AS REQUIRED AS2293 CLASSIFICATION C0-D8 - C90-E3.2.	WHITE	CLEVERTRONICS LUB PRO SM	A
SWITCH PANEL 1 (SP1)		WALL MOUNTED MULTI GANG SWITCH PANEL MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
SWITCH PANEL 2 (SP2)		WALL MOUNTED MULTI GANG SWITCH PANEL MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
LIGHTING CONTROL CHANNELS		LIGHTING CONTROL CHANNEL WITH ONE MANUAL SWITCH ON THE ASSOCIATED SWITCH PANEL PER SWITCH			A
ONE-WAY LIGHT SWITCH		ONE-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
CAT 6 COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO THE COMMUNICATIONS RACK CR-A TERMINATED ONTO FACILITY PATCH PANELS VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
COMMUNICATIONS RACK CR-A		PROVIDE A NEW COMMUNICATIONS RACK CR-A C/W FIBER AND 12 CORE FIBRE FROM THE EXISTING NISSAN BUILDING RACK UPGRADE THE NISSAN BUILDING FIBER AS REQUIRED. PROVIDE CR-A WITH PATCH PANELS TO ACCOMMODATE THE COMMUNICATIONS OUTLETS.			A



# ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: [www.edg.net.au](http://www.edg.net.au) Email: [brisbane@edg.net.au](mailto:brisbane@edg.net.au)

C3704a - EAGERS VW & CHERY, IPSWICH

C3704a-0002(A).xls

## ELECTRICAL EQUIPMENT SCHEDULE

REVISION A - 25 FEBRUARY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK  
[www.edg.net.au/Links/Lighting.htm](http://www.edg.net.au/Links/Lighting.htm)

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
SPECIAL PURPOSE OUTLET		SPECIAL PURPOSE OUTLET TYPE AS NOTED. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.			A
DOUBLE POWER OUTLET (USB)		DOUBLE POWER OUTLET C/W USB CHARGER AND CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT AB U.N.O. RATING 10A U.N.O.	WHITE	CLIPSAL 2000 SERIES + 30USBCM MECH	A
SIGN CONNECTION		COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE GPO / ISOLATORS ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW.			A
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT. "RSD" DENOTES ROLLER SHUTTER DOOR SUPPLY - COORDINATE LOCATION ONSITE WITH MOTOR.	-	CLIPSAL WHT35	A
FLOOR BOX TYPE 1 (FB1)		INSITU FLUSH FLOOR BOX C/W A DOUBLE GPOS+ FACILITY FOR A COMMUNICATIONS OUTLETS FACEPLATE. PROVIDE A 32 DIA CONDUIT C/W A SPARE DRAW WIRE FROM THE REAR OF THE COMMUNICATIONS FACEPLATE TO THE CEILING SPACE ABOVE THE COMMUNICATIONS RACK CR-A. PROVIDE THE GPOS AS PER THE STANDARD DESCRIPTIONS.	STAINLESS STEEL	ECD FB2SHD	A
DB-A		EXISTING DISTRIBUTION BOARD DB-A INTEGRAL TO THE EXISTING MSB TO BE UPGRADED WITH THE ADDITIONAL SWITCHGEAR AS PER THE DB-A SCHEDULE.			A
MSB		EXISTING MAIN SWITCHBOARD TO REMAIN AS IS.			A