



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S1	14W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION FIXED BEHIND THE TV AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700K PLUS R2380 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	B
S2	10W/M 2700K LED	IP67 LED FLEX SCREW FIXED ON THE SUSPENDED CEILING FEATURE AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	NATURAL	RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER	B
S3	10W/M 2700K LED	IP67 LED FLEX SCREW FIXED IN THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT.	NATURAL	RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER	B
S4	14.4W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED WITHIN THE CURTAIN PELMET TO ILLUMINATE THE CURTAIN AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700K PLUS R2381 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
S5	14.4W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION INTO THE REAR BAR JOINERY C/W DIFFUSER AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700K PLUS R2381 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
S6	14.4W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION INTO THE REAR BISTRO SERVERY JOINERY C/W DIFFUSER AS PER THE ELEVATION. MOUNT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700K PLUS R2381 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S7	RGB WW LED	LED RGB WW STRIPS WITHIN A SCREW FIXED EXTRUSION MOUNTED VERTICALLY ON EACH SIDE OF THE ENTRY AND ACROSS THE ENTRY CEILING AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE RGBWW DALI DRIVER / POWER SUPPLY SIZED TO ACCOMMODATE THE TOTAL STRIP LENGTH LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	BLACK HOUSING	NPA - SF16 RGB 3000K + HOUSING	A
S8	14.4W/M 2700K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED WITHIN THE COUNTER PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700K PLUS R2381 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
S9	14.4W/M 4000K LED	LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED UNDER THE OVERHEAD CUPBOARD AGAINST THE SPLASH BACK AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH A REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. SUPPLY AND SWITCH THE S18 WITH THE EXISTING ROOM LIGHTS.	WHITE	RAPID LED R2334 PLUS ALUMINIUM EXTRUSION AND DRIVER	B
PD01	3 X TRAILING EDGE DIMMABLE 240 VOLT 2200K B22 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP	1000 LONG DECORATIVE PENDANT TO BE CENTRED OVER THE POOL TABLE. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT	AGED SOLID COPPER	FAT SHACK VINTAGE CONE SWING PENDANT LIGHT SKU p439-SML-BLK	A
PD02	6 X TRAILING EDGE DIMMABLE 240 VOLT 2200K G9 LED 250 LUMENS +/- 10% 15,000 HOUR LIFE LAMP	1000DIA DECORATIVE PENDANT.	BRASS	ZEST LIGHTING ARCHED 6 LIGHT PENDANT	A
PD03	INTEGRAL TRAILING EDGE DIMMABLE LED	600DIA DECORATIVE PENDANT. CONFIRM THE SUSPENSION HEIGHT ONSITE WITH THE ARCHITECT	GYPSUM	BEACON LIGHTING MFL BALLARE 1 LIGHT PENDANT 017155	A
TL01	9W 2700K LED PER FITTING	SURFACE TRACK C/W FITTINGS AS INDICATED PROVIDE EACH TRACK WITH A REMOTE DALI DIMMABLE DRIVER LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	BLACK	LUMEN 8 NIX 45 TRACK AND SOLIS SON145TK09930 FITTINGS DALI DIMMABLE	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
WL01	2 X TRAILING EDGE DIMMABLE 240 VOLT 2700K 400LUMEN +/-10% E14 T125 LED	DECORATIVE 460 WIDE X 120 HIGH WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS ALLOW TO INSTALL	BRASS	ZEST LIGHTING BRASS SLIM ROUND TUBE FUNCTIONAL PICTURE WALL LIGHT	B
WL02	INTEGRAL TRAILING EDGE DIMMABLE LED	DECORATIVE 200 DIA WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS PROVIDE A PLYWOOD PANEL BEHIND THE LIGHT AS PER THE ARCHITECTURAL DETAIL	TRAVERTINE	FAT SHACK VINTAGE FAT HARMERS LED WALL LIGHT W1101- BEG-SML	A
WL03	2 X TRAILING EDGE DIMMABLE LED GU10 240 VOLT 2700K 250LUMEN +/-10%	150 H X 55MM DIA WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAIL MOUNT THE FITTING ON A TRADITIONAL ROUND TIMBER SINGLE SWITCH 90 DIA MOUNTING BLOCK, TO ENABLE WIRING TO RUN DOWN COPPER PIPING. THE WIRING TO EACH WL03 IS TO DROP VERTICALLY DOWN TOT HE FITTING WITHIN SURFACE MOUNTED COPPER CONDUIT FIXED TO THE BRICKWORK WALL USING COPPER SADDLES	COPPER FITTING MOUNTING BLOCK FINISH: PORTER'S PAINT LIQUID COPPER.	FAT SHACK VINTAGE PRODUCT NAME: DOUBL COPPER PIPE WALL LIGHT PRODUCT CODE: W034	A
WL04	TRAILING EDGE DIMMABLE GU10 LED 240 VOLT 2700K 200 LUMEN +/-10%	DECORATIVE WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS	BRUSHED COPPER	FAT SHACK VINTAGE BERTH OUTDOOR WALL LIGHT PRODUCT CODE: W198-CPR	A
WL05	2 X TRAILING EDGE DIMMABLE GU10 LED 240 VOLT 2700K 200 LUMEN +/-10%	DECORATIVE WALL LIGHT MOUNTED AS PER THE ARCHITECTURAL DETAILS	NATURAL	BEACON LIGHTING TRAVIATO 2 LIGHT UP/DOWN WALL SCONCE IN TRAVERTINE PRODUCT CODE: SKU 307011	A
WL06	450LUMEN 2700K LED	SURFACE MOUNTED ADJUSTABLE DOWNLIGHT C/W REMOTE DALI DIMMABLE POWER SUPPLY IT IS ACCEPTABLE TO USE A SUITABLY SIZED SINGLE POWER SUPPLY / DALI CONTROLLER TO SUPPLY MULTIPLE L7 FITTINGS ON THE SAME CHANNEL. LOCATE THE POWER SUPPLY AND DALI CONTROLLER IN A CONCEALED ACCESSIBLE POSITION WITH THE LOCATION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	BLACK	NPA L-FX-SL-ARA- SP1106-12V-27K-D	A
UL01	REPLACE THE EXISTING GROUND MOUNTED FITTINGS WITH LIKE FOR LIKE				A
UL02	REPLACE THE EXISTING GROUND MOUNTED FITTINGS WITH LIKE FOR LIKE				A
RD01	15W 2700K LED	RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER	BLACK	RAPID R1077-WH- 12W-2700-DALI	A

C3747a-0002(C).xls

Pages inc. any attach. 3 of 7



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
RD02	18W 2700K LED	RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1352-WH-18W-2700-DALI	A
RD03	12W 3000K LED	RECESSED IP54 DOWNLIGHT C/W 90 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1042-12 DALI	A
RD04	15W 2700K LED	RECESSED ADJUSTABLE DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1074-WH-15W-XW-24 DALI	A
RD05	12W 3000K LED	RECESSED IP54 DOWNLIGHT C/W 90 DEG BEAM REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1042-12 DALI	A
RD06	18W 2700K LED	RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1352-WH-18-4000	A
RD07	18W 2700K LED	REPLACE THE EXISTING RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DRIVER	WHITE	RAPID R1352-WH-18W-2700	B
RD08	15W 2700K LED	REPLACE THE EXISTING RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DRIVER	BLACK	RAPID R1077-WH-12W-2700	B
SL01	40W 4000K LED	SURFACE MOUNTED IP65 1200 LONG BATTEN C/W INTEGRAL DRIVER	NA	RAPID R3540-S-TRI	A
SL02	25W 3000K LED	SURFACE MOUNTED CAN DOWNLIGHT C/W REMOTE DALI DIMMABLE DRIVER	WHITE	RAPID R1147-WH-WH-36-SM-DALI	A
GL01	12W 2700K LED	GARDEN ELV SPIKE LIGHT. PROVIDE EACH GROUP OF GL01 FITTINGS WITH A REMOTE COMMON DALI DIMMABLE POWER SUPPLY. LOCATE DALI CONTROLLER /POWER SUPPLY IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	BLACK	GAMMA ILLUMINATION RULLO 1373-FL-2700K-12W-24V+ 373	A
RT01	30W 4000K LED	RECESSED 300 X 1200 PANEL LIGHT C/W RECESS KIT AND REMOTE DRIVER	WHITE	RAPID LED R3206-TRI-RM	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	CLEVERTRONICS LLIFE	A
E2	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	BLACK	CLEVERTRONICS LLIFEBLK	A
E3	LED	EMERGENCY LIGHT: SURFACE MOUNTED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	BLACK	CLEVERTRONICS LLIFESMBLK	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2	WHITE	CLEVERTRONICS LUBPRO-SM	A
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2	BLACK	CLEVERTRONICS LUBPRO-SM-BLK	A
HL01	1050WATT	1200 LONG LINEAR HEAT LAMP C/W CUSTOM SUPPORT AND INTEGRAL SWITCH MOUNTED UNDER THE UPPER SHELF AS PER THE ARCHITECTURAL DETAIL ALL CABLING IS TO BE CONCEALED	SILVER	ROBAND HQ1200E	A
HL02	1050WATT	1200 LONG LINEAR HEAT LAMP C/W CUSTOM SUPPORT AND INTEGRAL SWITCH MOUNTED UNDER THE LOWER SHELF AS PER THE ARCHITECTURAL DETAIL ALL CABLING IS TO BE CONCEALED	SILVER	ROBAND HQ1200E	A
CHANNEL x		CONTROL CHANNEL WITH A NUMERICAL REFERENCE. REFER TO THE POWER AND LIGHTING CONTROL SCHEMATIC / SCHEDULE			A
ONE-WAY LIGHT SWITCH		ONE-WAY LIGHT SWITCH C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES FACEPLATE	A
LIGHTING CONTROL SWITCH PANEL (SPx)		6-BUTTON PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE.	ALUMINIUM	DYNALITE ANTUMBRA DISPLAY	A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
MANUAL DALI POT DIMMER / LIGHT SWITCH (DIM)		DALI POT C/W INTEGRAL 20 DALI DEVICE POWER SUPPLY . FACTORY SET POWER ON RETURN TO LAST LEVEL.	WHITE	SMARTSCAPE DALI RD20 CLIPSAL C2000	A
EXISTING CEILING FAN (FE)		EXISTING CEILING FANS AND ITS ASSOCIATED CONTROLS TO BE RETAINED.			A
NEW CEILING FAN TYPE 1 (F01)		1400 DIA CEILING FAN TO BE PROVIDED WITH A DEDICATED FAN CONTROLLER	MATTE BLACK	VENTAIR SPYDC1423BL	C
NEW CEILING FAN TYPE 2 (F02)		900 DIA CEILING FAN TO BE PROVIDED WITH A DEDICATED FAN CONTROLLER . CONFIRM THE SUSPENSION LENGTH ON SITE WITH THE ARCHITECT	MATTE BLACK	VENTAIR SPYDC903BL	C
FAN CONTROLLER (FC)		ON OFF LOW MEDIUM HIGH FAN CONTROLLER WALL MOUNTED AT 1000 AFFL . ENSURE THE CONTROLLER IS COMPATIBLE WITH THE FAN.	WHITE	CLIPSAL C2000 SERIES FACEPLATE	A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. . RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. . RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SIGN CONNECTION		COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE CONNECTION ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW.			A
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. . RATING 20A U.N.O. . CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. . RATING 20A U.N.O. . CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	A
DB-L		PROVIDE A NEW DISTRIBUTION BOARD DB-L AS PER THE DB-L SCHEDULE AND NOTES. . PROVIDE A REMOVABLE HAT SECTION FROM THE TOP OF THE DISTRIBUTION BOARD TO THE CEILING. THE HAT SECTION IS TO BE OF THE SAME MATERIAL, COLOUR DEPTH AND WIDTH AS THE DISTRIBUTION BOARD. LOCATE DB-L INTERNALLY ON LEVEL 1 WITH THE POSITION AGREED ON SITE WITH THE ALH PROJECT MANAGER			A
DB-P		PROVIDE A NEW DISTRIBUTION BOARD DB-P AS PER THE DB-P SCHEDULE AND NOTES. . PROVIDE A REMOVABLE HAT SECTION FROM THE TOP OF THE DISTRIBUTION BOARD TO THE CEILING. THE HAT SECTION IS TO BE OF THE SAME MATERIAL, COLOUR DEPTH AND WIDTH AS THE DISTRIBUTION BOARD. LOCATE DB-P INTERNALLY ON LEVEL 1 WITH THE POSITION AGREED ON SITE WITH THE ALH PROJECT MANAGER			A



ELECTRICAL DESIGN GROUP

ELECTRICAL BUILDING SERVICES CONSULTANTS

P.O. Box 15, SHERWOOD Q. 4075

Phone: (07) 3278 4375 Fax: (07) 3716 0222

Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3747a - MELBOURNE HOTEL, BUNDABERG

C3747a-0002(C).xls

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 19 MAY 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK
www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
MSB		EXISTING HOTEL MAIN SWITCH BOARD TO BE MODIFIED AS PER THE MSB ELEVATION AND NOTES			A
DB-CJB		GAMING DISTRIBUTION BOARD TO BE PROVIDED BY GAMING ELECTRICIAN			A