ELECTRICAL DESIGN GROUP
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3763a - REDLANDS SPORTING CLUB - STAGE 2 **C3763a-0002(C).xls**

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 04 NOVEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
L1	14W 4000K	600 X 300 LAY IN FLAT PLATE LED FITTING C/W REMOTE DRIVER MOUNTED IN A FLUSH RECESSED PLASTER BOARD KIT	WHITE TRIM	GAMMA ILLUMINATION AXIS 1550-4K-14W	C
L2	26W 4000K	600 x 600 LAY IN FLAT PLATE LED FITTING C/W REMOTE DRIVER MOUNTED IN A FLUSH RECESSED PLASTERBOARD MOUNTING KIT	WHITE TRIM	GAMMA ILLUMINATION AXIS 1548-4K-26W C/W FLUSH RECESS PB KIT	A
FS01	1W LED AT 500 CENTRES	FESTOON LIGHTS WITH NEW 24V DC IP65 FESTOON LIGHTING TO BE FIXED TO A 316 STAINLESS STEEL WIRE SUPPORT SYSTEM. SUPPLY THE NEW FESTOON LIGHTS VIA REMOTE DALI DIMMABLE DRIVERS IN A CONCEALED ACCESSIBLE POSITIONS NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE LENGTH AND POSITION ON SITE	BLACK CABLE AND FIXINGS 316 STAINLESS STEEL SUPPORT AND FIXINGS	FIRE FLY FFC-LS-50-24VE27-BK	A
EXIST	EXISTING FITTING OR OUTLET TO REMAIN AS IS UNLESS NOTED OTHERWISE				A
PD01	7W 2700K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT G95 E27 LED	DECORATIVE 360 DIA LIGHT PENDANT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	BLACK	FAT SHACK VINTAGE P321-LRG	A
PD02	INTEGRAL 2700K TRAILING EDGE DIMMABLE LED	DECORATIVE 1500 LONG LIGHT PENDANT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT REMOTE DRIVER	GALVANISED	EDISON LIGHT GLOBES 1500MM PIPE LOOP LED TUBE LIGHT C/W ALUMINIUM SHADE AND OPAQUE TUBE COVER	A
PD03	3 X 25W 2200K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT G125 B22 LED	DECORATIVE 1100 LONG LIGHT PENDANT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	VINTAGE STEEL C/W BLACK CAGE GUARD	FAT SHACK VINTAGE P442-VST-BLK	A
PD04	3 X 7W 2700K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT G95 E27 LED	DECORATIVE 700 DIA LIGHT PENDANT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT	BLACK	DISCOUNT LIGHTING SAONA-3L BLACK	A
RDE	EXISTING RECESSED DOWNLIGHT TO REMAIN AS IS UNLESS NOTED OTHERWISE				A
WL01	7W 2700K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT A60 B22 LED	DECORATIVE 520 HIGH WALL LIGHT CONFIRM THE POSITION AND MOUNTING HEIGHT ON SITE WITH THE ARCHITECT	BLACK	FAT SHACK VINTAGE W1126-BLK-SML-BLK	A
WL02	2 X 6W 2200K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT B22 ST64 TEARDROP LED	DECORATIVE 660 HIGH UP DOWN WALL LIGHT CONFIRM THE POSITION AND MOUNTING HEIGHT ON SITE WITH THE ARCHITECT	BLACK	FAT SHACK VINTAGE SKU W017-BLK-FRS	B

ELECTRICAL DESIGN GROUP
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3763a - REDLANDS SPORTING CLUB - STAGE 2 **C3763a-0002(C).xls**

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 04 NOVEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
RD01	18W 2700K LED	185 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	BLACK	RAPID R1355-WH-18W-XW DALI	B
RD02	15W 2700K LED	75 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	BLACK	RAPID R1075-BK-15W-XW-60 DALI	A
RD03	15W 2700K LED	75 DIA RECESSED ADJUSTABLE DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER	BLACK	RAPID R1074-BK-15W-XW-60 DALI	A
RD04	15W 2700K LED	REPLACE THE EXISTING DOWN LIGHT WITH A 75 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER THE EXISTING CABLING NEEDS TO BE REPLACED.	WHITE	RAPID R1075-BK-15W-XW-60 DALI	A
S1	14.4W/M 2700K LED	HORIZONTAL RUN OF LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE FRONT FACE OF THE BAR COUNTER JOINERY AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
S2	14.4W/M 2700K LED	HORIZONTAL RUN OF LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE SPORTS BAR REAR JOINERY AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	B
S3	NO LONGER REQUIRED				B
S4	14.4W/M 2700K LED	HORIZONTAL RUN OF LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE SPORTS BAR BIG SCREEN WALL AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A

ELECTRICAL DESIGN GROUP BRISBANE PTY LTD ACN 092 710 793
TRADING AS – ELECTRICAL DESIGN GROUP ABN 96 092 710 793

ELECTRICAL DESIGN GROUP
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3763a - REDLANDS SPORTING CLUB - STAGE 2 **C3763a-0002(C).xls**

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 04 NOVEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
S5	14.4W/M 2700K LED	HORIZONTAL RUN OF LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE SPORTS BAR ENTRY JOINERY AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS.	NATURAL	RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER	A
E1	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	BLACK	CLEVERTRONICS LLIFE BLK	B
E2	LED	EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40.	WHITE	CLEVERTRONICS LLIFE	B
EX	LED	EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D8 - C90-E3.2.	BLACK UNLESS NOTED AS WHITE	CLEVERTRONICS LUBPRO-SM BLK	B
FIRE EVACUATION SPEAKER		BLACK RECESSED 5W TWO-TONE 8-INCH CONE ALERT AND EVACUATION SPEAKER TO AS1670.1 C/W 100V MULTI-TAP TRANSFORMER AND FLUSH GRILLE . WH INDICATES THE SPEAKER IS TO BE PROVIDED AS WHITE.			A
SMOKE DETECTOR		BLACK SURFACE MOUNTED SMOKE DETECTOR TO AS1670.1. WH INDICATES THE DETECTOR IS TO BE PROVIDED AS WHITE.			A
LIGHTING CONTROL SWITCH PANEL (SP1)		EXISTING DYNALITE LIGHTING CONTROL PANEL TO BE RECOVERED PRIOR TO DEMOLITION AND REINSTALLED.			A
CHANNEL x		CONTROL CHANNEL WITH A NUMERICAL REFERENCE. REFER TO THE POWER AND LIGHTING CONTROL SCHEMATIC / SCHEDULE			A
COMMUNICATIONS OUTLET		RJ45 CAT-6 COMMUNICATIONS OUTLET, CABLED BACK TO A PATCH PANEL IN COMMUNICATIONS CABINET CR-A VIA 4-PAIR CAT-6 UTP CABLE. MOUNT UP TO 3 RJ45 OUTLETS PER MULTI-GANG FACEPLATE WITH SEPARATE PERMANENT LABELLING FOR EACH OUTLET. MOUNT AT 300 AFFL U.N.O	WHITE UNLESS CEILING MOUNTED THEN BLACK	CLIPSAL C2000 SERIES	B
COMMUNICATIONS RACK (CR-A)		EXISTING COMMUNICATIONS RACK TO BE UPGRADED AS NECESSARY INCLUDING NEW PATCH PANELS TO ACCOMMODATE THE ADDITIONAL COMMUNICATIONS OUTLETS. ALL EXISTING CABLING MADE REDUNDANT BY THE WORKS IS TO BE REMOVED. THE NEW PATCH PANELS AND PORT NUMBERING IS TO MATCH THE EXISTING.			A
SINGLE POWER OUTLET		SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A

ELECTRICAL DESIGN GROUP BRISBANE PTY LTD ACN 092 710 793
TRADING AS – ELECTRICAL DESIGN GROUP ABN 96 092 710 793

ELECTRICAL DESIGN GROUP
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

C3763a - REDLANDS SPORTING CLUB - STAGE 2 **C3763a-0002(C).xls**

ELECTRICAL EQUIPMENT SCHEDULE

REVISION C - 04 NOVEMBER 2026

THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm

TYPE	LAMPS	DESCRIPTION	COLOUR / ACCESSORY	CATALOGUE No	REV
DOUBLE POWER OUTLET		DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O.	WHITE UNLESS NOTED AS BLACK (BK)	CLIPSAL C2000 SERIES	A
SPECIAL PURPOSE OUTLET		SPECIAL PURPOSE OUTLET TYPE AS NOTED. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.			A
SIGN CONNECTION		COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE GPO / ISOLATORS ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW.			A
SINGLE-PHASE ISOLATOR		SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT20	A
THREE-PHASE ISOLATOR		THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT.	-	CLIPSAL WHT35	A
DB-B		EXISTING DISTRIBUTION BOARD DB-B TO BE PROVIDED WITH A NEW 63A THREE PHASE MCB TO SUPPLY DB-B1. THE EXISTING SWITCHGEAR MADE REDUNDANT BY THE WORKS IS TO BE REMOVED.			A
DB-B1		NEW DISTRIBUTION BOARD DB-B1 TO BE PROVIDED AS PER THE DB-B1 SCHEDULE AND THE NOTES. PROVIDE A SHOP DRAWING OF DB-B1 FOR APPROVAL.			A
DB-C		EXISTING DISTRIBUTION BOARD DB-C TO BE MODIFIED AS PER THE DB-C SCHEDULE AND THE NOTES. THE EXISTING SWITCHGEAR MADE REDUNDANT BY THE WORKS IS TO BE REMOVED.			B
GOLF SIMULATOR CLOCK (CLK)		PROVIDE A WALL MOUNTED RECESSED CLOCK FACEPLATE AS PER THE GOLF SIMULATOR SHOP DRAWINGS. PROVIDE A CONCEALED 40 DIA CONDUIT C/W DRAW WIRE FROM THE CLOCK FACE PLATE TO THE GOLF SIMULATOR COMPUTER.			A
GOLF SIMULATOR PROJECTOR (GSP)		PROVIDE A CONCEALED 40 DIA CONDUIT C/W DRAW WIRE FROM THE CEILING SPACE ADJACENT THE GOLF SIMULATOR CEILING PROJECTOR TO THE GOLF SIMULATOR COMPUTER. LOCATE THE PROJECTOR AS PER AS PER THE GOLF SIMULATOR SHOP DRAWINGS.			A
GOLF SIMULATOR HITTING SCREEN (GSH)		PROVIDE A CONCEALED 40 DIA CONDUIT C/W DRAW WIRE FROM THE WALL ADJACENT THE GOLF SIMULATOR HITTING SCREEN TO THE GOLF SIMULATOR COMPUTER. LOCATE THE HITTING SCREEN CONDUIT POINT AS PER AS PER THE GOLF SIMULATOR SHOP DRAWINGS.			A
GOLF SIMULATOR ION CAMERA (ION)		PROVIDE A CONCEALED 40 DIA CONDUIT C/W DRAW WIRE FROM THE CEILING SPACE ADJACENT THE GOLF SIMULATOR ION CAMERA TO THE GOLF SIMULATOR COMPUTER. LOCATE THE ION CAMERA AS PER AS PER THE GOLF SIMULATOR SHOP DRAWINGS.			A
GOLF SIMULATOR COMPUTER (GSC)		GOLF SIMULATOR COMPUTER ARRANGED AS PER AS PER THE GOLF SIMULATOR SHOP DRAWINGS.			B

ELECTRICAL DESIGN GROUP BRISBANE PTY LTD ACN 092 710 793
TRADING AS – ELECTRICAL DESIGN GROUP ABN 96 092 710 793