1101 TUBO



SPECIFICATIONS:	0.9 kg	82+ 3K and 4K	70+ 5K	Tilt 15°	Class I	IP40	CE	Available	5 Year warranty	Made in Australia

CONSTRUCTION & DESIGN

- Surface mounted LED adjustable downlight
- Constructed in aluminium alloy and finished in durable polyester powdercoat paint

OPTICAL & THERMAL PERFORMANCE

- Customised housing provides premium optical and thermal performance
- Wide beam distribution with no harsh cut off and ultra low glare

ELECTRICAL SYSTEM

- Supplied standard with an integral leading and trailing edge mains dimmable driver and terminal block, compatible with a range of dimming systems
- Power factor > 0.9 with active power factor correction
- Input voltage 220-240V, 50/60 Hz

TECHNICAL PERFORMANCE

- 8W or 13W total system power consumption with overload and short circuit protection
- >65,000 hours lifespan (L70)
- Premium quality LED Module with high lumen output per watt
- Chromaticity tolerance (MacAdam step) - 2
- Available in 3K, 4K or 5K colour temperature with very low colour shift over time

CODE ORDERING GUIDE: PRODUCT CODE - COLOUR CODE

Example: 1101-SP-3K-8W-01

SYSTEM POWER	COLOUR TEMP.	24° SP	36° FL	47° WFL	55° VWFL	HOT LED LUMENS	LUMINAIRE LUMEN OUTPUT			
		PRODUCT CODE					SP	FL	WFL	VWFL
8W	3K	1101-SP-3K-8W	1101-FL-3K-8W	1101-WFL-3K-8W	-	828	697	690	696	-
	4K	1101-SP-4K-8W	1101-FL-4K-8W	1101-WFL-4K-8W	-	870	727	738	756	-
	5K	1101-SP-5K-8W	1101-FL-5K-8W	1101-WFL-5K-8W	-	845	719	711	718	-
13W	3K	1101-SP-3K-13W	1101-FL-3K-13W	-	1101-VWFL-3K-13W	1519	1274	1275	-	1270
	4K	1101-SP-4K-13W	1101-FL-4K-13W	-	1101-VWFL-4K-13W	1607	1339	1335	-	1322
	5K	1101-SP-5K-13W	1101-FL-5K-13W	-	1101-VWFL-5K-13W	1568	1312	1290	-	1296

COLOUR CODE	
-01	Satin White
-06	Matte Black
-10	Bright Silver

