**ELECTRICAL DESIGN GROUP**
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**
**ELECTRICAL EQUIPMENT SCHEDULE**
**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK**
**www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| S1 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED SURFACE MOUNTED TO RUNS FROM THE GROUND TO THE TOP OF THE EXTERNAL FEATURE AS PER THE ELEVATION AND THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S2 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER SURFACE MOUNTED ABOVE THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S3 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED ANGLED EXTRUSION C/W DIFFUSER SURFACE MOUNTED ABOVE THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS R2380 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S4 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED ANGLED EXTRUSION C/W DIFFUSER SURFACE MOUNTED ABOVE THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS R2380 ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S5 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER SURFACE MOUNTED WITHIN THE CEILING PELMET AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S6 | 10W/M 2700K LED | TWO RUNS PER STRUCTURAL ELEMENT OF IP67 LED FLEX SCREW FIXED TO RISE VERTICALLY THEN HORIZONTALLY UP AND ACROSS THE ARBOUR AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |



ELECTRICAL DESIGN GROUP BRISBANE PTY LTD ACN 092 710 793
TRADING AS – ELECTRICAL DESIGN GROUP ABN 96 092 710 793

**ELECTRICAL DESIGN GROUP**
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**
**ELECTRICAL EQUIPMENT SCHEDULE**
**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| S7 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S8 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S9 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S10 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED TO RISE VERTICALLY UP THE WALL THEN HORIZONTALLY UP AND ACROSS THE CEILING AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S11 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED RECESSED INTO THE BAR COUNTER FRONT AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S12 | 14.4W/M 2700K LED | MULTIPLE LED STRIPS WITHIN SCREW FIXED EXTRUSIONS C/W DIFFUSER RECESSED INTO THE REAR DISPLAY JOINERY AS PER THE ARCHITECTURAL DETAIL. REFER TO THE ELEVATIONS FOR THE QUANTITY AND EXTENT. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |

**ELECTRICAL DESIGN GROUP**
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**
**ELECTRICAL EQUIPMENT SCHEDULE**
**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| S13 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED BEHIND THE MIRROR AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S14 | 10W/M 2700K LED | IP67 LED FLEX SCREW FIXED TO THE FRONT EDGE OF THE COLUMN TO RISE VERTICALLY AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE POWER SUPPLY LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE BEND PLANE (TOP OR SIDE) ON SITE WITH THE ARCHITECT. | WHITE | RAPID LED R2321 OR R2322 - 2700K + POWER SUPPLY & DALI CONTROLLER | A |
| S15 | 14.4W/M 2700K LED | MULTIPLE LED STRIPS WITHIN SCREW FIXED EXTRUSIONS C/W DIFFUSER RECESSED INTO THE REAR DISPLAY JOINERY AS PER THE ARCHITECTURAL DETAIL. REFER TO THE ELEVATIONS FOR THE QUANTITY AND EXTENT. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S16 | 14.4W/M 2700K LED | LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER RECESSED INTO THE SERVERY COUNTER SKIRTING AS PER THE ARCHITECTURAL DETAIL. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| S17 | 14.4W/M 2700K LED | MULTIPLE LED STRIPS WITHIN SCREW FIXED EXTRUSIONS C/W DIFFUSER RECESSED INTO THE REAR DISPLAY JOINERY AS PER THE ARCHITECTURAL DETAIL. REFER TO THE ELEVATIONS FOR THE QUANTITY AND EXTENT. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |
| RT2 | 14.4W/M 2700K LED | REPLACE THE EXISTING FLUORESCENT COFFER LIGHTING WITH LED STRIP WITHIN A SCREW FIXED EXTRUSION C/W DIFFUSER MOUNTED WITHIN THE EXISTING COFFER RETAINING THE EXISTING COFFER DIFFUSER. PROVIDE THE STRIP WITH REMOTE DALI DIMMABLE POWER SUPPLIES AS REQUIRED LOCATE THE POWER SUPPLIES IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | NATURAL | RAPID LED R2334 2700 K PLUS ALUMINIUM EXTRUSION OPAL DIFFUSER AND POWER SUPPLY & DALI CONTROLLER | A |

**ELECTRICAL DESIGN GROUP**
**ELECTRICAL BUILDING SERVICES CONSULTANTS**
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**
**ELECTRICAL EQUIPMENT SCHEDULE**
**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| RD01 | 15W 2700K LED | 75 DIA PIN HOLE RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER | BLACK | RAPID R1077-BK-15W-XW-DALI | A |
| RD02 | 15W 2700K LED | 70 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER | BLACK | RAPID R1075-BK-15W-XW-DALI | A |
| RD03 | 15W 2700K LED | 70 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1075-WH-15W-XW-DALI | A |
| RD04 | 15W 2700K LED | 75 DIA PIN HOLE RECESSED DOWNLIGHT C/W 24 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1077-WH-15W-XW-DALI | A |
| RD11 | 15W 2700K LED | 70 DIA RECESSED DOWNLIGHT C/W 60 DEG BEAM REMOTE DALI DIMMABLE DRIVER | WHITE | RAPID R1075-WH-15W-XW-DALI | A |
| G1 | GAMING BASE KICK LED STRIP LIGHTS TO BE PROVIDED AS PART OF THE GAMING BASE AND CONNECTED BY THE GAMING ELECTRICIAN. | | | | A |
| G2 | GAMING SCREEN LED STRIP LIGHTS TO BE PROVIDED AS PART OF THE GAMING SCREENS AND CONNECTED BY THE GAMING ELECTRICIAN. | | | | A |
| FS01 | 1W LED AT 500 CENTRES | FESTOON LIGHTS WITH NEW 24V DC IP65 FESTOON LIGHTING TO BE FIXED TO A 316 STAINLESS STEEL WIRE SUPPORT SYSTEM. SUPPLY THE NEW FESTOON LIGHTS VIA REMOTE DALI DIMMABLE DRIVERS IN A CONCEALED ACCESSIBLE POSITIONS NOTED ON THE AS CONSTRUCTED DOCUMENTS. CONFIRM THE LENGTH AND POSITION ON SITE ENSURE THE FESTOON LIGHTS ARE LOWER THAN THE ADJACENT CEILING FANS | BLACK CABLE AND FIXINGS 316 STAINLESS STEEL SUPPORT AND FIXINGS | FIRE FLY FFC-LS-50-24VE27-BK | A |
| E1 | LED | EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40. | BLACK | CLEVERTRONICS LLIFE-BLK | A |
| E2 | LED | EMERGENCY LIGHT: RECESSED NON-MAINTAINED EMERGENCY LIGHT. AS2293 CLASSIFICATION C0-D40 - C90-D40. | WHITE | CLEVERTRONICS LLIFE | A |

**ELECTRICAL DESIGN GROUP**
**ELECTRICAL BUILDING SERVICES CONSULTANTS**
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**
**ELECTRICAL EQUIPMENT SCHEDULE**
**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK**
**www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| EX | LED | EXIT LIGHT: MAINTAINED 24M VIEWING DISTANCE EXIT LIGHT C/W DIFFUSERS & DIRECTIONAL ARROWS AS SHOWN. CEILING SURFACE MOUNT OR WALL MOUNT BETWEEN 2100mm & 2700mm AFFL IF THERE IS NO VERTICAL SURFACE TO MOUNT THE FITTING ON WITHIN THIS RANGE CONFIRM THE MOUNTING HEIGHT WITH THE ENGINEER. AS2293 CLASSIFICATION C0-D1.25- C90-D2 | BLACK UNLESS NOTED AS WH THEN WHITE BODY | CLEVERTRONICS LUBPRO-SM-BLK | A |
| F02 | CEILING FAN | EXISTING CEILING FAN TO BE REPLACED 60 INCH CEILING FAN C/W MOUNTING THAT ALLOWS THE FAN TO HANG TRUE AND A REMOTE CONTROLLER WALL MOUNTED ADJACENT SP1. CONFIRM THE DROP ON SITE WITH THE ARCHITECT | WHITE / WHITE | BIG ASS HAIKU OUTDOOR | B |
| PDE | EXISTING DECORATIVE POOL TABLE PENDANT LIGHT TO BE RETAINED AND RESUPPLIED AS INDICATED. | | | | A |
| PD01 | INTEGRAL TRAILING EDGE DIMMABLE 2700K LED | DECORATIVE PENDANT LIGHT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT | BLACK | LIGHTING COLLECTIVE ARLC004PL - 002 | B |
| PD02 | 7W 2700K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT A60 ES LED | DECORATIVE PENDANT LIGHT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT | WHITE | LIGHTING COLLECTIVE FNOR030PL - 001 | B |
| PD03 | INTEGRAL TRAILING EDGE DIMMABLE 2700K LED | DECORATIVE PENDANT LIGHT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT | ASH | FAT SHACK VINTAGE LP050-NAT | B |
| PD04 | 7W 2700K 240V TRAILING EDGE DIMMABLE EXPOSED FILAMENT A60 ES LED | DECORATIVE PENDANT LIGHT CONFIRM THE POSITION AND DROP LENGTH ON SITE WITH THE ARCHITECT ALLOW TO INSTALL ALLOW A PC SUM FOR THE SUPPLY OF EACH FITTING | TBA | ALLOW A PC SUM OF $250.00 FOR THE SUPPLY OF EACH PD04 FITTING | B |
| TL01 | 9W 2700K LED PER FITTING | SURFACE TRACK C/W FITTINGS AS INDICATED PROVIDE EACH TRACK WITH A REMOTE DALI DIMMABLE DRIVER LOCATED IN A CONCEALED ACCESSIBLE POSITION NOTED ON THE AS CONSTRUCTED DOCUMENTS. | BLACK | LUMEN 8 NIX 45 TRACK AND SOLIS SON145TK09930 FITTINGS DALI DIMMABLE | A |
| CHANNEL x | | CONTROL CHANNEL WITH A NUMERICAL REFERENCE. REFER TO THE POWER AND LIGHTING CONTROL SCHEMATIC / SCHEDULE | | | A |
| LIGHTING CONTROL SWITCH PANEL 1 (SP1) | | PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE. | WHITE | DYNALITE ANTUMBRA DISPLAY | B |



ELECTRICAL DESIGN GROUP BRISBANE PTY LTD ACN 092 710 793
TRADING AS – ELECTRICAL DESIGN GROUP ABN 96 092 710 793

**ELECTRICAL DESIGN GROUP**
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**
**ELECTRICAL EQUIPMENT SCHEDULE**
**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK**
**www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| LIGHTING CONTROL SWITCH PANEL 2 (SP2) | | PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE. | BLACK | DYNALITE ANTUMBRA DISPLAY | B |
| LIGHTING CONTROL SWITCH PANEL 3 (SP3) | | PROGRAMMABLE SWITCH PANEL C/W CENTRAL LCD DISPLAY MOUNTED AT 1000mm AFFL UNLESS NOTED OTHERWISE. | BLACK | DYNALITE ANTUMBRA DISPLAY | B |
| SINGLE POWER OUTLET | | SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O. | WHITE UNLESS NOTED AS BLACK (BK) | CLIPSAL ICONIC SERIES | A |
| AUTO DOOR SINGLE POWER OUTLET (AD) | | SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION LOCATED CONCEALED WITHIN THE AUTO DOOR HEAD MULLION RATING 10A U.N.O. | WHITE | CLIPSAL ICONIC SERIES | A |
| IP56 SINGLE POWER OUTLET | | SINGLE POWER OUTLET C/W CIRCUIT IDENTIFICATION LOCATED CONCEALED WITHIN THE AUTO DOOR HEAD MULLION RATING 10A U.N.O. | WHITE | CLIPSAL ICONIC SERIES | A |
| DOUBLE POWER OUTLET | | DOUBLE POWER OUTLET C/W CIRCUIT IDENTIFICATION ON THE FACEPLATE BEHIND THE SURROUND MOUNT AT 300mm AFFL U.N.O. RATING 10A U.N.O. | WHITE UNLESS NOTED AS BLACK (BK) | CLIPSAL ICONIC SERIES | A |
| SINGLE WEATHERPROOF POWER OUTLET (IP56) | | IP56 WEATHERPROOF SINGLE POWER OUTLET. MOUNT AT MINIMUM 1100mm AFFL U.N.O. RATING 10A U.N.O. | - | CLIPSAL "56 SERIES" | B |
| SIGN CONNECTION | | COORDINATE THE LOCATION AND CONNECTION WITH THE SIGN CONTRACTOR ENSURING THE GPO / ISOLATORS ARE PROVIDED WITH APPROPRIATE WEATHER PROTECTION AND ARE CONCEALED FROM VIEW. | | | A |
| SINGLE-PHASE ISOLATOR | | SINGLE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT. | - | CLIPSAL WHT20 | A |
| THREE-PHASE ISOLATOR | | THREE-PHASE WEATHERPROOF ISOLATOR. MOUNT AT 1350mm AFFL U.N.O. RATING 20A U.N.O. CONNECT TO EQUIPMENT VIA FLEXIBLE CONDUIT. | - | CLIPSAL WHT35 | A |
| DB-G | | GAMING DISTRIBUTION BOARD TO BE PROVIDED BY THE GAMING ELECTRICIAN. | | | A |
| DB-2 | | EXISTING DISTRIBUTION BOARD DB-2. ALL EXISTING CIRCUITS THAT BECOME REDUNDANT ARE TO BE REMOVED. | | | A |
| DB-3 | | PROVIDE A NEW DISTRIBUTION BOARD DB-3 AS PER THE DB-3 SCHEDULE AND NOTES. | | | A |

**ELECTRICAL DESIGN GROUP**
ELECTRICAL BUILDING SERVICES CONSULTANTS
P.O. Box 15, SHERWOOD Q. 4075
Phone: 0418 893 338
Web Site: www.edg.net.au Email: brisbane@edg.net.au

**C3855a - VICTORIA POINT TAVERN** **C3855a-0002(B).xls**

**ELECTRICAL EQUIPMENT SCHEDULE**

**REVISION B - 30 OCTOBER 2026**

**THE LIGHT FITTING SUPPLIER CONTACT DETAILS MAY BE AVAILABLE ON THE EDG WEBSITE VIA THE FOLLOWING LINK www.edg.net.au/Links/Lighting.htm**

| TYPE | LAMPS | DESCRIPTION | COLOUR / ACCESSORY | CATALOGUE No | REV |
|---|---|---|---|---|---|
| FIRE INDICATOR PANEL (FIP) | | EXISTING FIP TO BE REPLACED WITH A NEW SURFACE MOUNTED WHITE AS 1670.1 COMPLAINT FIRE INDICATOR PANEL INCORPORATING THE EWCIE AND FDCIE. PROVIDE THE FIP WITH A MANUAL CALL POINT AND A SCREW FIXED MECHANICALLY ENGRAVED ZONE PLAN | | | A |
| SMOKE DETECTOR | | SURFACE MOUNTED AS7240.7 POINT SMOKE DETECTORS WITH A PERFORMANCE OF 6 TO 12 % OBS/M SET AT 7.8 %. WHITE UNLESS NOTED AS (BK) THEN BLACK. | | | A |
| RECESSED FIRE ALARM SPEAKER | | RECESSED 5W TWO-TONE 8-INCH CONE ALERT AND EVACUATION SPEAKER TO AS1670.1 C/W 100V MULTI-TAP TRANSFORMER AND GRILLE WHITE UNLESS NOTED AS (BK) THEN BLACK. | | | A |
| FIRE ALARM DOOR INTERFACE | | INTERFACE THE FIRE DETECTION SYSTEM TO THE DOOR CONTROL SYSTEM SUCH THAT THE DOOR IS UNLOCKED VIA A FAIL SAFE SIGNAL UPON ALARM. | | | A |



ELECTRICAL DESIGN GROUP BRISBANE PTY LTD ACN 092 710 793
TRADING AS – ELECTRICAL DESIGN GROUP ABN 96 092 710 793